

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 24S RANGE 2W SEC. 528 PLSS # 400226

Date: 1/12/26 By: KE
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 12-11-25

Map: _____

Narrative: _____

Corner Rpt: CS 6716-53

Corner Designation

S 1/16 528/527

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

1 1/4" I.D. Iron pipe
Proj 13"

Condition report

Not Found

Renewed

Unrecorded

Surveyed In

Previous Renewals

Mcchesney 1927 CS 53/110-7

MONUMENT DETAIL

1/4" I.D Iron Pipe

Accessories Found

Burned - Broken 24" Cedar Stump N49°W
40.9 FT TO W NAIL

DEAD 32" CEDAR N17°E 32.6 FT (REC 30.3 FT)
ADD 3 1/2" MAG NAIL RIGHT SIDE CENTER

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

18" SAWN FIR STUMP 530°W 17.3 FT
 ADD 3 1/2" MAG NAIL Top Center

Sketch of Monument, Accessories, and General Area

Location & Comments

COR. IS APPROX 400 FT EAST
 OF LOGGING LANDING
 IN FLAT CLEARCUT

AREA BURNED
 9/2020

Trimble GEO XT POSITION
 43° 45272407 N
 122° 93165540 W

Comp. Decline. 14 1/4° E
 Agency DCSE
 Party Chief S. F. HAUSE
 Note keeper
 Witnesses J. LORSUNG

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Ronald A. Quimby

OREGON
 JULY 14, 1978
 RONALD A. QUIMBY
 1654

EXPIRES: 12/31/2026

CS 67161-63 pg 2/4

DECLINATION 14 1/4° E

RENEWED 12-11-26

T24S, R2W, 400220

TRIMBLE GEO XT POSITION, W.P.S.

ACCESSORIES ADDED THIS DATE:

43.

122.

	BEARING-	FEET	ORIG. BT	W-NAIL	PLATE	BRASS DISC
26" CEDAR ✓ BROKEN BURNED	S 49° W ✓	40.9 ✓	TO "W" NAIL	X	X	
18" CEDAR ✓ STUMP "W" NAIL IN FACE	N 17° E ✓	30.3 ✓		X	X	
32" - DEAD STANDING		32.6 ✓				
ADD 3 1/2" MAG NAIL R.S.C. TO STANDING 32" CEDAR						

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

DESCRIPTION OF GROUND COVER AND GROUND SLOPE AT CORNER: A: EAST REEF CUT

FIRE TRAIL

FROM CORNER NORTH: 52° OC TO WEST LOGGED TO EAST

SOUTH: 152° LOGGED TO EAST AND TO WEST

EAST: LEVEL 90° LOGGED TO WEST AND SOUTH

WEST: 52° 90° SP. BR. FLOWS SOUTH, CENTER TO NORTH

LOGGED TO SOUTH

ML 6-45
CS 53/110-7
this
CS 40/110-2
53/110-3-4

WORK DONE FOR W. T. CO.

BY: Shaw McChesney
ENGINEER - SURVEYOR

DATE: OCTOBER 24, 1957

ASSISTED BY:

NEW 18" X 3 1/2 FT SAWN FIR STUMP
S 30° W, 17 3/4 SET 3 1/2" MAG NAIL TOP CENTER

(1957 SEE PG. 1)
FOUND MONUMENT
UNDER SUPERVISION OF:
1 1/4" I.D. IRON PIPE
PROT. 13

COPIES SENT TO:

CORNER LIES APPROX 400 FT EAST
OF LOGGING LANDING IN FLAT
CLEARCUT.

CSUT/61-63 pg 14

SEAL

