GOVERNMENT CORNER RESTORATION FORM

FILED
Date: 11/2/26 By: KC
This survey consists of:
Map:
Narrative:
Corner Rpt: CS 40/110-54
DOUGLAS COUNTY SURVEYOR

TOWNSHIP 24S RANGE 2W SEC. 28 PLSS # 360220

DOUGLAS COUNTY OREGON DATE 12-17-25

Corner Designation SE 1/4 Sec 28

Monument(s) Found: (Condition and Source)

1 1/2" Iron pipe Leaning Approx 1' South Returned To plumb position up 4"

Previous Renewals

Hosford CS 40/110 1953

Hosford 1957 CS 42/304-8

__ Condition report
__ Not Found
✓ Renewed
__ Unrecorded
__ Surveyed In

MONUMENT DETAIL

Accessories Found

Metal Post 1 FT South

pg 1/3

C.S. File CS 40/110-54

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

SAWN - Burnt 19" x 1FT FIR Stump
S40°E 4.4 FT 3½" MAG NAIL Top Center

Burnt - SAWN 12" x 1½ FT FIR Stump
S 60°W 8.5 FT 3½" MAG NAIL RIGHT
Side Center

Sketch of Monument, Accessories, and General Area

MON on Gentle South Slope
Approx 40 FT South of A
GRAVEL ROAD

Trimble G5 DXT Position
43.45191653 N
122.93626834 W

Location & Comments

MON IN very
Recent Clearcut
AREA Burnt
9/2020

Comp. Decline. 14¼° E
Agency DCSD
Party Chief S. FLAUSE
Note keeper
Witnesses J. Lorsung

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

CS 67/61-84 pg 2/3

MINI GPS
43.45187
122.93626

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 360220

PRIMARY CORNER DESCRIPTION SE 1/16 Cor. Sec. 28

Alias _____ Description _____
Alias _____ Description TRIMBLE GEO XT POSITION
Alias _____ Description _____
Alias _____ Description 43.45191053°N
DECLINATION 14¼°E 122.93626834°W RENEWED 12/17/25

V.W. Hosford - Dec. 1953 - C.S. File 40/110

Set - 4" Hemlock post for corner.
NO EVIDENCE A Hemlock, 10", bears N.32½°E., 27.8 ft., mkd: 1/16 S28 PS 253 BT.
" " A Cedar, 10", bears East 31.1 ft., mkd: 1/16 S28 PS 253 BT.

V.W. Hosford - Sept. 1957 - C.S. File 42/306-8

At the SE 1/16 S28, the BTs marked in my survey of 1953 are in good condition. At the true point of the corner I drove a 1½" iron pipe 30" long 18" in the ground. FOUND LEANING APPROX. 1 FT. SOUTH (See C.S. 42/306-8 for E1/16 secs 28/33 & S1/16 secs 28|27
A LINE OF METAL LATH RUNS NORTH TO MON. AND N76¼°E AWAY FROM MON.
THE 1½"×30" IRON PIPE IS RETURNED TO PLUMB NOW PROT. 4"

NEW REFERENCES: FOUND METAL LATH SOUTH, 1 FT.

A BURNED AND SAWN 19" DIA. X 1 FT. FIR STUMP WITH A 3½" MAG NAIL SET TOP CENTER; BEARS S40°E, 4± FT. DIST.

A BURNED AND SAWN 12" DIA. X 1½ FT. FIR STUMP WITH SPIKE NAIL R.S.C.; BEARS S64°W, 8± FT. DIST.

MONUMENT IS IN VERY LARGE, REGENT, CLEARCUT.
MONUMENT ON A GENTLE SOUTH SLOPE APPROX. 40 FT SOUTH OF A GRAVEL RD.

CS 40|61-64 pg 3|3