

TOWNSHIP 255 RANGE 2W SEC. 8

PLSS # 30054

Date: 1/28/26 By: KC
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 1-7-26

Map: _____

Narrative: _____

Corner Rpt: CS 67/61-60

Corner Designation

1/4 COR 8/9

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

3/4" BLM BRASS PROJ
6" IN ROUGH MOUND OF
STONE

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

Hosford 1958 CS 42/398
Machaney 1959 CS 53/112-6
BLM RESURVEY 1962 Vol 32 pg 13253
BLM 2014-2015 Vol 58 pg 23341

MONUMENT DETAIL

1/4
58/59
T255R2W
1962

Accessories Found

BURNED - Broken 13" X 12 FT D. FIR SWAG
N 85° E 9.0 FT (Rec S 88 1/2° E 9.1 FT) PARTLY
HEATED SINGLE BLAZE ILLEGIBLE SCRIBES
VISIBL

13" X 12 FT 9" D. FIRE WAY OUT OF POSITION
DOWNHILL NO ROOT HOLE PARTLY HEATED SINGLE
BLAZE ILLEGIBLE SCRIBES VISIBL

New Accessories

5/8" x 30" iron with DCSO plastic cap
proj 2" N 24°E 9.1 FT

Burned Broken off 13" x 6' FT D. FIRE SWAG
S 32°E 27.5 FT

Burned Broken off 12" x 5 FT D. FIRE SWAG
N 18° W 15.1 FT

Both new BT'S have 3 1/2" mag nail Right
Side Center

Sketch of Monument, Accessories, and General Area

Location & Comments

MON ON Steper S.W slope
Approx 165 FT West of
Gravel Road

AREA BURNED
9/2020

Trimble GEO XT position

43.40968587 N
122.95322825 W

Comp. Decline. 14/14°E
Agency DCSO
Party Chief S. KAUSE
Note keeper
Witnesses J. LORSON

CS 67161-60 pg 2/5

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1854

EXPIRES: 12/31/2026

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

MINI GIS
43,40968
122,95323

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3636)

Set basalt stone 20x10x6", 15" in the ground for 1/4 sec. cor. marked 1/4 on W face, from which

A hemlock, 12" dia., bears S.70°E., 10 lks., mkd: 1/4 S9 BT.
A dogwood, 6" dia., bears S.30 1/2°W., 13 lks., mkd: 1/4 S8 BT.

FD. stone & 1 live BT by V. Hosford Aug/Oct. 1958 C.S. File 42/398

Glen McChesney, WEYCO - 3/24/1959 - C.S. File 53/112-6

Found - 18" hemlock, 2 faces not opened recently, S.71°E., 6.2 ft. (ADDED "W" nail & plate)
10"x3' dogwood stub & new 4" sprouts coming up from root, S.31°W., 8.6 ft
New - 16" sugar pine, N.47°W., 15.4 ft. "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13235)

The 1/4 sec. cor, of secs. 8 & 9, monumented with a basalt stone, 20x10x8", firmly set 15" in the ground, mkd on the W face, from which the original bearing trees:

A hemlock, 25" dia., bears S.70°E., 10 lks, with a healed blaze.

A dogwood crown, bears S.30 1/2°W., 13 lks., with fragmentary scribe marks, in negative, visible on rotted trunk,

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground with brass cap marked

1/4
S 8 | S 9
T25S R2W
1962

from which a new bearing tree

A W.Pine, 19" dia., bears N.49 1/4°W., 25 lks., mkd S8 BT.

Deposit the original corner stone alongside the iron post.

DECLINATION 14 1/4°E

RENEWED 01/07/26

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23341)

The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above the ground, with a brass cap (properly) mkd

VA 3 1/4" B.C. / 2" I.D.I.P PROT 6"

MONUMENT IS IN A ROUGH MOUND OF STONE

CS 67161-600

1
pg 315

BURNED N. FIR SNAG 12" x 5 FT 15 1/2, N18° W

" " 13" x 6 FT. 275, S32° E

IR PROTZ 9 1/2, N24° E

MOD SW SLOPE

CLEAR CV - NE QUART REST BURNED 100 FT

CS 67/61-60 pg 4/5

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION: 1/4 Cor Secs 8 & 9

Alias _____ Description _____

Alias _____ Description TRIMBLE GEO XT POSITION

Alias _____ Description _____

Alias _____ Description 43.40968587°N

122.95322825°W

from which the remains of a BT mkd. by McChesney, Weyerhaeuser Timber Co., in 1959 and reported by Brooks in 1962 as a new bearing tree

~~gone~~ ~~SLIDE AT LOCATION~~ — A decayed sugar pine stump, 20" dia., bears N.44 $\frac{1}{4}$ °W., 16.5 ft., with scribe marks $\frac{1}{4}$ S8 BT visible on a decayed blaze. (Record, white pine, N.49 $\frac{1}{2}$ °W.)

and new bearing trees

N 85° E

A D. Fir \checkmark 12" dia., bears ~~S. 80 $\frac{1}{2}$ ° E.~~ N 85° E, 9.0 ft., mkd. $\frac{1}{4}$ S9 BT. PH 5B

~~A D. Fir \checkmark 8" dia., bears N. 3° W., 4.6 ft., mkd. $\frac{1}{4}$ S8 BT. ILLEG. SCR BG.~~

9"

NO ROOTHOLE

PH 5B ILLEG SCR BG

WAY OUT OF POSITION DOWN HILL

NEW REF.S:

A 5/8" x 30" I.R. / DCSO SET PROT. 2 INCHES ABOVE GROUND; BEARS N 24° E, 9 $\frac{1}{2}$ FT. DIST.
PLASTIC CAP

A BURNED BROKEN OFF 13" x 6 FT TALL D. FIR SNAG; BEARS S 32° E, 27 $\frac{1}{2}$ FT. DIST.

" " " " 12" x 5 FT. TALL D. FIR SNAG; BEARS N 18° W, 15 $\frac{1}{2}$ FT. DIST.

BOTH NEW B.T.S HAVE A 3 $\frac{1}{2}$ " MAG NAIL R.S.C.

MONUMENT ON STEEPER SW SLOPE APPROX 165' WEST OF GRAVEL RD.