

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 25S RANGE 2W SEC. 7

PLSS # 200520 Date: 2/4/20 By: KE

This survey consists of:

DOUGLAS COUNTY OREGON

DATE 1-28-20

Map: _____

Narrative: _____

Corner Rpt: CS 07/02-08

Corner Designation

S 1/16 57/58

DOUGLAS COUNTY SURVEYOR

Monument(s) Found: (Condition and Source)

3/4" BLM BRASS CAP
proj 3" steel post
on South Edge

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

Set by HOSFORD 1958
BLM RESURVEY 2010 Vol
57 pg 22797-98

MONUMENT DETAIL

S 1/16
57/58
2010

Accessories Found

SAWN - BURNED 32" X 6 FT CEDAR STUMP
S83°W 20.1 FT (Rec S84°W 19.0 FT)
"W" NAIL OFF CENTER OF FACE BEARS S86°W
18.8 FT FACE mostly burned off low
AXE MARKS REMAIN
Fallen BURNED 14" Hemlock No MEASURABLE
POSITION REMAINS partly Healed single
BLAZE No scribes visible
BURNED Broken off shattered 10" X 3 FT
Hemlock STUMP N7°W 17.8 FT FACE
Burned off

New Accessories

Burned - SAWN 18" X 2 FT Hemlock Stump
566° E 14.2 FT 3 1/2" MAG Nail Top Center
over Root Crown

Sketch of Monument, Accessories, and General Area

Location & Comments

MON on moderately steep
NNE slope in strip of
Burnt Forest running N.W
Rest of AREA Large Clearcut
Trimble Geo XT Position
43° 40616920 XI
122° 97262521 XI

MON IS APPROX
450 FT EAST OF
GRAVEL ROAD

AREA BURNT
9/2020

Comp. Decline. 14 1/4° E
Agency DLSD
Party Chief S. F. HAUSE
Note keeper
Witnesses J. ZORSUNY

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

CS 67162-08

pg 2/5

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	S 7 1/4 ——— S 18 T 25 S R 2 W 1962
	from which the remains of an original bearing tree A hemlock stump, 28 ins. diam., bears S. 12 1/4° W., 39.4 ft. dist., with a healed blaze. (Record, S. 16° W., 40.9 ft. dist.) and the remains of a bearing tree mkd. by Brooks A sawed hemlock stump, 16 ins. diam., bears N. 50° W., 51.5 ft. dist., with a healed blaze and a metal cover. and bearing trees mkd. by the Douglas County Surveyor's Office A fir, 5 ins. diam., bears N. 28 1/4° E., 8.2 ft. dist., with a healed double blaze. A chinquapin, 7 ins. diam., bears S. 89° E., 9.9 ft. dist., with scribe marks 1/4 S18 CS BT visible on a partially healed double blaze. A fir, 22 ins. diam., bears S. 50° E., 3.4 ft. dist., with a healed double blaze.

	S. 83° 05' 17" W., beginning new measurement, continue posting and blazing.
90	Graveled road, 15 ft. wide, bears N. 75° W. and S. 55° W.
225	Graveled road, 12 ft. wide, bears N. 40° E. and S. 40° W.
1935.73	The closing cor. of secs. 7 and 18 only, on the W. bdy. of the Tp.
	Discontinue posting and blazing <i>DECLINATION 14 1/4° E</i> <i>RENEWED 1/28/26</i>
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0° 03' 37" E., bet. secs. 7 and 8, posting and blazing.
1329.25	The S 1/16 sec. cor. of secs. 7 and 8, established by Vernon W. Hosford, Oregon PLS No. 253, in 1957, and is accepted as the cor., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, from which the remains a bearing tree mkd. by Hosford
	<i>SAWN, BURNED 32" x 6 FT STUMP</i> A sawed, decayed cedar stump, <i>33 ins. diam., bears S. 84° W., 19.0 ft. dist., with a healed blaze and a "W" nail in lower chaining notch. "W" NAIL OFF CENTER OF FACE BEARS S86° W, 188 FT. DISTANT. FACE MOSTLY BURNED OFF LOW AXE MARKS REMAIN.</i>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>and bearing trees of unknown origin</p> <p><i>FALLEN BURNED 14" DIAM.</i> A hemlock 11 ins. diam., bears S. 62 1/2° W., 21.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. <i>NO MEASURABLE POSITION REMAINS</i></p> <p><i>NOW BROKEN OFF SHATTERED AND BURNED 10" x 3 FT. STUMP</i> A hemlock 10 ins. diam., bears N. 7° W., 17.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. <i>PHS B NO SCRIBING SEEN</i></p> <p><i>NEW REFERENCE:</i> At the corner point <i>SAWN BURNED 18" x 2 FT. HEMLOCK STUMP WITH A 3 1/2" MAG NAIL IN TOP CENTERED OVER ROOT CROWN BEARS S 66° E, 14 1/2 FT. DISTANT</i></p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p><i>3 1/4" B.C. S 1/16 V PROT. 3 INCHES</i> S 7 S 8 2010</p> <p><i>GALVANIZED STEEL LATH FOUND ON SOUTH EDGE</i> Deposit a magnet in a white plastic case at the base of the stainless steel post. <i>MONUMENT ON MODERATELY STEEP NNE SLOPE IN STRIP OF BURNED FOREST RUNNING NW'LY, REST OF AREA A LARGE CLEARCUT MONUMENT IS APPROX. 450 FT EAST OF A GRAVEL ROAD.</i></p> <p>N. 0° 04' 48" E., beginning new measurement, continue posting and blazing.</p>
435	Creek, 1 ft. wide, course S. 65° E.
1328.99	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, (alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground), with brass cap mkd.</p> <p style="text-align: center;">1/4 S 7 S 8 T 25 S R 2 W 1962</p> <p>from which the remains of an original bearing tree</p> <p>A roothole bears N. 33° W., 9.9 ft. dist., alongside of which is a fallen yew trunk, 11 ins. diam., with no marks visible on a decayed blaze.</p> <p>and the remains of accessories mkd. by Brooks</p> <p>A roothole bears N. 44 1/2° E., 75.2 ft. dist., alongside of which is a fallen yew trunk, 16 ins. diam., with no marks visible.</p> <p>A rock outcrop bears S. 68 1/2° W., 12.5 ft. dist., mkd. X BO. (Record, S. 73° W., 13.2 ft. dist.)</p> <p>and new bearing trees</p> <p>A fir, 17 ins. diam., bears S. 37° E., 20.1 ft. dist., mkd. 1/4 S8 BT.</p>