

TOWNSHIP 25S RANGE 2W SEC. 18

PLSS # 140400

Date: 2/24/24 By: LC

This survey consists of:

DOUGLAS COUNTY OREGON

DATE 2-18-24

Map: _____

Narrative: _____

Corner Rpt: CS 67162-15

Corner Designation

1/4 COR 518
519

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

3 1/4" BLM BRASS CAP
ON 2 1/2" I.P. PROJ 2"

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

BLM Resurvey 1962 Vol 32 pg 132A

Perkins 1982 CS 67/23-8

DCSO 1989 CS 62/63-8

Quimby 2014 M 167-34 AEB

BLM Resurvey 2014-2015

Vol 58 pgs 23344-45

MONUMENT DETAIL

1/4 518
519

T25S R2W

Accessories Found

SAWN-BURNED 22" X 2 FT INCENSE CEDAR STUMP

N72°E 32.3 FT ADD 3 1/2" MAG NAIL RIGHT

Side Center

SAWN BURNED 11" X 2 FT HEMLOCK STUMP S14°W

2.2 FT (REC 54.W) ADD 3 1/2" MAG NAIL RIGHT

Side Center

SAWN-BURNED 22" X 2 1/2 FT CEDAR STUMP (REC

HEMLOCK) S 81 1/2° W 22.0 FT (REC 26.5 FT)

FACE VISIBILE INSIDE ADD 3 1/2" MAG NAIL

Top Center

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

BURNED - SAWN 12" X 1 1/2 FT FIR STUMP N 29° E
10.7 FT 3 1/2" MAG NAIL TOP CENTER

Sketch of Monument, Accessories, and General Area

Location & Comments

MON ON moderate west slope
IN VERY LARGE NEWER CLEARCUT
MON IS APPROX 125 FT WEST
OF GRAVEL ROAD
TRIMBLE GEO XT POSITION
43° 378992 N.
122° 9827983 W.

AREA BURN

9-2020

Comp. Decline: 14 1/4° E
Agency DCSO
Party Chief S. FANISE
Note keeper
Witnesses J. LORSON

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

CS 67162-15

pg 2/3

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____	Description <u>TRIMBLE GEO XT POSITION</u>
Alias _____	Description _____
Alias _____	Description <u>43.38789992°N</u>
Alias <u>DECLINATION 14 1/4° E</u>	Description <u>22.98279813°W</u>

RENEWED 2/18/26

FOUND 3 1/4" B.C. MARKED AS DESCRIBD. IN 1962 ON 2 1/2" I.P. PROT 2 INCHES.

SAWN BURNED 22" x 3 1/2" STUMP

An incense cedar stump, 34" dia., bears N. 72 1/2° E., 32.3 ft., with no marks visible and a "W" nail in face at the base of the stump. ~~GONE~~ ADD 3 1/2" MAG NAIL R.S.C.

SAWN BURNED 11" x 2" BACK BURNED OUT

A hemlock, 14" dia., bears S. 4° W., 2.2 ft., with a healed blaze. ~~GONE~~ ADD 3 1/2" MAG NAIL R.S.C.

BURNED SAWN 22" x 2 1/2" STUMP

and BTs mkd. by the Douglas County Surveyor's Office
A ~~hemlock~~ CEEDAR, 16" dia., bears S. 81 1/2° W., 26.5 ft. with a healed double blaze. ~~GONE~~ FACE SEEN INSIDE. 22" ADD 3 1/2" MAG NAIL TOP CNTR.

GONE NO EVIDENCE

The southerly-most trunk of a multi-trunk madrone snag, 7" dia., bears N. 53° W., 17.2 ft., with a healed upper blaze and scribe mark B visible on a partially healed lower blaze.

NEW REFERENCE:

A SAWN AND BURNED 12" x 1 1/2" FT. TALL FIR STUMP, WITH A 3 1/2" MAG NAIL SET TOP CENTER, BEARS: N 29° E, 10 1/2 FT. DISTANT.

MONUMENT IS ON MODERATE WEST SLOPE IN A VERY LARGE NEWER CLEARCUT. MONUMENT IS APPROX. 125 FT. WEST OF A GRAVEL ROAD.