

TOWNSHIP 24S RANGE BW SEC. 20 PLSS # 240340

Date: 2/05/06 By: ke
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 3-19-26

Map: _____
Narrative: _____
Corner Rpt: CS 67/102-26

DOUGLAS COUNTY
SURVEYOR

Corner Designation

2 1/4 S 20

Monument(s) Found: (Condition and Source)

3 1/2" UNSTAMPED BRASS
CAP ON IRON PIPE

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

JULIADO 1969 CS 55/120: M38-48
Hostetter 2006 CS 65/58-10

MONUMENT DETAIL

Accessories Found

20" Hemlock S60°E 33.9 FT TO SPIKE
IN FACE below scribes PARTLY HEALED
SINGLE BLAZE Illegible Scribes VISIBLE

16" Hemlock N27°W 43.8 FT TO SPIKE
IN FACE PARTLY HEALED SINGLE BLAZE
scribing VISIBLE

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

Unrecorded 65" D. FIR 521°W 19.2 FT
Not Blazed but Tagged 3 1/2" MAG
Nail in Face

Sketch of Monument, Accessories, and General Area

Location & Comments

Trimble GEO XT Position

43° 46851352 XI

123° 67348967 W

Comp. Decline. 14 1/4° E
Agency DCSO
Party Chief S. R. PAUSE
Note keeper
Witnesses J. Zorsung

CS 67162-26 pg 2/3

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 20

Alias _____	Description _____
Alias _____	Description <u>TRIMBLE GEO XT POSITION</u>
Alias _____	Description _____
Alias _____	Description <u>43,46851352</u>
	<u>123,67348987</u>

Survey by Nick Juliano - For: Weyerhaeuser Co. - Sept. 1969
-C.S. File 55/120 and M 38-48

The center of sec. 20 was determined by the intersection of the N-S and E-W center lines of said section.

Set 2" Iron pipe with brass cap.

Referenced with "W" nails:

36" Fir S.21°W., 19.2 ft.

40" Fir N.22°E., 9.3 ft.

DECLINATION 14 1/4° E

RENEWED 3/19/26

Tony Hostetter - For: Weyerhaeuser Co - 3/2006 - CS 65/58-10

Found - 2" ^{3 1/2" UNSTAMPED PROT 6"} iron pipe w/brass cap & both BTs set by Juliano in 1969 (M 38-48).

New BTs ^{20"} 18" hemlock ^N scribed "S20 C 1/4 BT", tagged, bears; S.60°E ^V, 33.9 ft ^V to spike placed below scribing ^V

^{16" 12"} hemlock ^N scribed "S20 C 1/4 BT", tagged, bears ^V N.27°W ^V, 43.8 ft ^V to spike placed below scribing ^V

BLAZE FACES S 75° E BUT SPIKE IS ORIENTED TO CORNER AND NOT BELOW SCRIBING

PHSB ILLEG. SCRIBING
PHSB ILLEG. SCRIBING VIS.

FOUND BT:

65" D. FIR NOT BLAZED BUT TAGGED BEARS S 21° W, 192 (AS PER TAG)
ADD 3 1/2 MAG NAIL TO FACE, TOP OF NAIL AT RECORD DISTANCE FROM B.C.

MINI GIS
43,46851
123,67347

CS 67/62-26

pg 3/3