

TOWNSHIP 24S RANGE 8W SEC. 29 PLSS # 260206

Date: 8/25/20 By: llc
This survey consists of:

DOUGLAS COUNTY OREGON DATE 3-19-20

Map: _____
Narrative: _____
Corner Rpt: CS(07)102-27

Corner Designation
sec COR 30 | 29
31 | 32

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)
3/14" BLM BRASS CAP
Proj 8"

___ Condition report
___ Not Found
 Renewed
___ Unrecorded
___ Surveyed In

Previous Renewals
BLM Resurvey 1962 Vol 32 pg 13331-32
Johnstone 1983 M 95-41

MONUMENT DETAIL
T24S 8W
530 | 529
531 | 532
1962

Accessories Found
Fallen - Burned - Rotted FIR 5N49 560°E
29.0 FT Root Hole

14" MADRONE N 48 1/2° E 22.4 FT Partly Healed
Single BLAZE Some Illegible Scribings
Visible AND 3 1/2" MAG NAIL RIGHT SIDE CENTER

BROKEN OFF ROTTED 25" x 3 1/2 FT FIR STUMP
S 36° W 28.0 FT (REC 44 LKS) All scribes
Visible

25" D. FIR S 32 1/2° E 29.4 FT (REC 44 LKS) Fully
Healed Single BLAZE ADD 3 1/2" MAG NAIL
RIGHT SIDE CENTER

UNRECORDED 13" D. FIR Scribed T28 S 28 W
S 31° W Single BLAZE BEARS S 34° W 29.0 FT
3 1/2" MAG NAIL RIGHT SIDE CENTER

New Accessories

15" D. FIRE N 15° E 6.5 FT scribed BT ON
LOW BLAZE HAS LINE BLAZES ON
WEST EDGE 3 1/2" MAG NAIL RIGHT
SIDE CENTER

Sketch of Monument, Accessories, and General Area

Location & Comments

BIS MAP POSITION

43° 44' 22" N
123° 68' 34" W

Comp. Decline. 14 1/4° E
Agency DCSO
Party Chief S. F. HUSE
Note keeper
Witnesses J. LORSUNG

CS 47/42-27 pg 2/4

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

Alias _____	Description _____
Alias _____	Description <u>GIS MAP POSITION (POOR SATELLITES FOR GPS TIE)</u>
Alias _____	Description _____
Alias _____	Description <u>43.44682</u>
	<u>123.68354</u>

MINI GIS
43.44681°N
123.68354°W

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3366)

Set a sandstone 14 x 12 x 7 ins., 9" in the ground, for cor. to secs. 29, 30, 31 and 32, marked with 1 notch on S. and 5 notches on E. edges, from which

- A Laurel 12" dia., bears N.34°E., 36 lks. dist. mkd. T24S R8W S29 BT.
- A Cedar 18" dia., bears S.65°E., 37 lks. dist. mkd. T24S R8W S32 BT.
- A Laurel 16" dia., bears S.60°W., 20 lks. dist. mkd. T24S R8W S31 BT.
- A Fir 12" dia., bears N.13°W., 31 lks. dist. mkd. T24S R8W S30 BT.

DECLINATION 14 1/4° E RENEWED 3/19/26

BLM resurvey by C. Albert White, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13331-32)

The Sec. cor., determined at record distance from the remains of three original bearing trees and at the intersection of the original N. and S. and E. and W. blazed lines: from which the original bearing trees:

ROTTEN BURNED 13"
GONE NO EVIDENCE
GONE NO EVIDENCE

- A Madrone stump hole bears N.50°E., 36 lks. dist. (Rec. N.34°E.) **FALLEN**
- A burned Fir snag 14" dia., bears S.60°E., 44 lks. dist. **NEAR ROOT HOLE** **NO BLZ. EVID.**
- ~~A Madrone stump hole bears S.64°W., 20 lks. dist. (Rec. S.60°W.)~~
- ~~A rotted Fir stump bears N.23°W., 31 lks. dist. (Rec. N.13°W.)~~

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

	T 24 S R 8 W	
<u>3 1/4" BC</u>	S 30 S 29	<u>PROT 8"</u>
	S 31 S 32	
	1962	

ADD 3 1/2" MAG NAIL R.S.C. TO NE AND SE B.T.S.

from which

- 14" A Madrone 13" dia., bears N.48 1/2° E., 34 lks. dist. mkd. T24S R8W S29 BT. **PHSB, SOME**
- 25" A Fir 8" dia., bears S.32 1/2° E., 45 lks. dist. mkd. T24S R8W S32 BT. **FACE INTACT ALL SCRIBING VISIBLE**
- 25" x 3 1/2' A Fir 18" dia., bears S.36°W., 44 lks. dist. mkd. T24S R8W S31 BT. **280**

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

~~GONE~~ A Fir 6" dia., bears N.50°W., 14⁵⁷/₂ lks. dist. mkd. T24S R8W
NO EVIDENCE S30 BT.

Fd. OK, Nov. 1983 by H. Johnstone - M 95-41

NEW UNRECORDED BT (WEYERHAEUSER)
↓ SHOULD BE 24

A 13" DIA. D. FIR SCRIBED "T28SR8WS31" ON A SINGLE BLAZE; BEARS
S34°W, 24° FT. DISTANT (WEYERHAEUSER TAG READS 25³/₄' N34°E, T28SR8WS31)
ADD A 3 1/2" MAG NAIL R.S.C.

NEW REE:

15" D. FIR SCRIBED "BT" ON LOW BLZ, HAS LINETREE BLAZES ON WEST EDGE
BEARS N15°E, 6⁵/₈ FT. DIST. SET 3 1/2" MAG NAIL R.S.C.

CS 67142-27 pg 4/4