

TOWNSHIP 26S RANGE 8W SEC. 10

PLSS # 500540

Date: 4/1/20 By: KE
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 3-25-26

Map: _____
Narrative: _____
Corner Rpt: CS67102-31

Corner Designation

1/4 COR 10/11

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" DC SO BRASS CAP
Proj 6"

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

DC SO 1968 CS 54/72-20

MONUMENT DETAIL

COUNTY SURVEYORS
OFFICE
26S 8W
1/4 510/511
1968

Accessories Found

18" YEW N 61° W 23.3 FT (Rec N 65° W 25.0 FT)
blaze decayed Add 3 1/2" mng Nail RIGHT
Side Center

26" Armitole N 68° E 2.4 FT Fully Healed
Double BLAZE Add 3 1/2" mng Nail RIGHT
Side Center

39" Hemlock S 79° W 19.1 FT No BLAZE visible
ADD 3 1/2" mng Nail RIGHT Side Center

New Accessories

Fd Two unrecorded Weyerhaeuser
2008 B.T.S

1 1/2" Hemlock N45°W 20.9 FT Scribed 1/4 510 BT
on partly healed single blaze spike
Nail below face Dist to tip of nail

1 1/2" Red Alder Bark scribed 1/4 510 BT
N6°W 16.5 FT spike nail Dist to
Tip Nail

Sketch of Monument, Accessories, and General Area

Location & Comments

Trimble GEO XT Position

43° 32337351 N

123° 62442819 W

MON APPROX
40 FT NORTH
OF GRAVEL
ROAD

Comp. Decline. 14 1/4° E
Agency DCSO
Party Chief S.F. HAUSE
Note keeper
Witnesses J. Korman

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

CS 67162-31 pg 2/3

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description <u>TRIMBLE GEO XT POSITION</u>
Alias _____	Description _____
Alias _____	Description <u>43.32337351°N</u>
	<u>123.62442819°W</u>

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4669)

 Set fir post, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd 1/4 S on W face, from which
 A fir, 18" dia., bears N.32°E., 62 lks., mkd: 1/4 S BT.
 A yew, 8" dia., bears N.65°W., 50 lks., mkd: 1/4 S BT.

DECLINATION 14'14"E

RENEWED 3/25/26

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones & W. Penley - Aug. 1968- C.S. File 54/72-20

~~GONE NO EVIDENCE~~
 Found - ~~Orig. 18", now 30" Fir, alive, N.32°E. 40.9 ft., bark~~
 scribe in poor condition. 61° 333
18"-Orig. 8", now 14" Yew, alive, N.65°W. 33.0 ft. blaze
 decayed, no scribing. ADD 3 1/2" MAG NAIL R.S.C.

Set - Brass Cap at Cor. Mkd: County Surveyors T26S R8W Office, 1968 2 1/2" BC S 10 | S 11

PROT. 6"

New BTs - 26" 7" Hemlock N. 68° E, 2.4 ft, Mkd: "1/4 S11 CS BT" FHDB
39" 18" Hemlock S. 79° W, 13.1 ft. Mkd: "1/4 S10 CS BT."

This corner lies on very gentle NW slope. BLZ NO LONGER VISIBLE

ADD 3 1/2" MAG NAIL R.S.C. TO THESE 2
TWO 1968 NEW B.T.S

ALSO FOUND TWO 2008 WEYERHAEUSER UNRECORDED B.T.S

A 14" DIA. HEMLOCK WITH A PHSTB SHOWING "1/4 S10 BT"; BEARS N45°W, 20⁹ FT. DIST, HAS SPIKE NAIL BELOW FACE, DIST. MEASURED FROM TIP OF NAIL

A 14" DIA. RED ALDER BARK SCRIBED "1/4 S10 BT"; BEARS N06°W, 16⁵ FT. DISTAKT HAS SPIKE NAIL AS ABOVE.

B.C MON. IS APPROX. 40 FT. NORTH FROM A GRAVEL ROAD.