

TOWNSHIP 25S RANGE 8W SEC. 515 PLSS # 460440

Date: 4/1/26 By: KE  
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 3-25-26

Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Corner Rpt: CS 67/62-32

Corner Designation

CE 1/16 S15

DOUGLAS COUNTY  
SURVEYOR

Monument(s) Found: (Condition and Source)

3/4" BLM BRASS CAP  
FLUSH WITH SURFACE

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

Set by BLM Vol 50  
Pgs 18880, 81

MONUMENT DETAIL

E 1/4 C  
S15  
1989

Accessories Found

26" X 5 FT Rotted FIR STUMP S58°E  
6.6 FT Fully Healed Single blaze

16" X 6 FT Rotted FIR STUMP N37 1/2°W  
46.9 FT Fully Healed Single blaze

3/4" Iron pipe N32 1/2°E 1.0 FT  
Set by unofficial BLM Administrative  
Survey in 1970

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

New Accessories

5/8" X 30" Iron Rod with DCSD  
PLASTIC CAP N46°W 34.6 FT SET  
PROJ 6" IN ROAD CUT BANK

Sketch of Monument, Accessories, and General Area

Location & Comments

MOON IN YOUNGER FIR  
PLANTATION APPROX 25 FT  
EAST AND 35 FT SOUTH OF  
GRAVEL ROAD

Trimble GEO XT POSITION

43. 39696078 N

123. 62953005 W

Comp. Decline. 14 1/4° E  
Agency DCSD  
Party Chief S KLAUSE  
Note keeper  
Witnesses J. Jorsund

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald A. Quimby*

OREGON  
JULY 14, 1978  
RONALD A. QUIMBY  
1654

EXPIRES: 12/31/2026

CS 67/62-32

pg 2/3

Subdivision of Section 15,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Descend over broken NW. slope.

58.30 Creek, 10 lks. wide, course E.; asc. over broken S. slope.

74.970 The 1/4 sec. cor. of secs. 10 and 15.

From the 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 25 S R 8 W  
1/4  
S 15 \* S 14  
1965

from which bearing trees mkd. by Beck and Jelley

A fir, 15 ins. diam., bears N. 78 1/2° E., 25 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 54 1/4° W., 8 1/2 lks dist., with healed blaze.

S. 87° 40' 00" W., on the E. and W. center line of sec. 15.

Descend over SW. slope, through heavy timber and dense undergrowth.

4.00 Gravel road, 30 lks. wide, bears NW. and SE.

6.00 Gravel road, 40 lks. wide, bears N. 15° W. and S. 15° E.

10.80 Ravine, drains S.; asc. over broken SE. slope.

19.110 Point for the center E 1/16 sec. cor. of sec. 15.

DECLINATION 14 1/4° E

RENEWED 3/25/26

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

3 1/4" BC E 1/16  
C ----- C FLUSH WITH SURFACE  
S 15  
1989

from which

26" x 5 FT. SAWN ROTTED STUMP A fir, 23 ins. diam., bears S. 58° E., 10 lks. dist., mkd. CE 1/16 S15 BT. FHSB

16" x 6 FT. SAWN ROTTED STUMP A fir, 15 ins. diam., bears N. 27 1/2° W., 7 1/2 lks. dist., mkd. CE 1/16 S15 BT. FHSB

OVER →

MINI GIS  
43.39647  
123.62955

TRIMBLE GEOXT POSITION  
43.39646078° N  
123.62953005° W

Subdivision of Section 15,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

MINI GIS  
43.39618  
123.63904

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point unofficially established by a Bureau of Land Management administrative survey in 1970, record held at Roseburg District Office, bears N. 82° 24' E., 0.015 chs. dist., monumented with an iron pipe, 3/4 in. diam., projecting 10 ins. above ground. TOP BENT EAST 8 FT.

NEW REF

5/8" x 30" IR / DCSD PLASTIC CAP. PROT. 6" IN RD. CUTBANK - N46° W, 346 FT, DISTANT  
Continue to ascend over broken SE. slope.

19.50

Gravel road, 40 lks. wide, bears N. 35° E. and S. 35° W.

MC MONUMENT IN YOUNGER FIR PLANTATION APPROX. 25 FT. EAST AND 35 FT. SOUTH FROM A GRAVEL RD.

26.30

Ridge, bears N. 80° E. and S. 80° W.; desc. over broken NW. slope.

38.220

The center 1/4 sec. cor. of sec. 15.

Along broken N. slope.

46.20

Begin ascent over broken NE. slope.

57.335

Point for the center W 1/16 sec. cor. of sec. 15.

420440

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16  
C ----- C  
S 15  
1989

from which

A fir, 7 ins. diam., bears S. 34° E., 6 lks. dist., mkd. X BT.

A fir, 27 ins. diam., bears N. 4° W., 29 lks. dist., mkd. CW 1/16 S 15 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point unofficially established by a Bureau of Land Management administrative survey in 1970, record held at Roseburg District Office, bears N. 21° 07' E., 0.047 chs. dist., monumented with an iron pipe, 3/4 in. diam., projecting 16 ins. above ground.

Continue to ascend over NE. slope.

59.00

Ridge, bears N. 70° W. and S. 70° E.; desc. over broken SW. slope.

74.70

Ravine, drains S.; asc. over SE. slope.