

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 24S RANGE 8W SEC. 11 PLSS # 600600

Date: 4/8/26 By: ke
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 3-31-26

Map: _____

Narrative: _____

Corner Rpt: CS67162-36

Corner Designation

NORTH CC S11|S12

DOUGLAS COUNTY
SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" DC SO BRASS CAP
PROJ 6"

___ Condition report

___ Not Found

Renewed

___ Unrecorded

___ Surveyed In

Previous Renewals

GLD SURVEY 1896 Vol 11 pgs 9660-1
DCSO 1968 CS 54/72-4
BLM RESURVEY 1971 Vol 17
PGS 15218 - 9
BLM RESURVEY 1983 Vol 43
PGS 16755

MONUMENT DETAIL

COUNTY SURVEYORS
OFFICE

T2LS RBW

CC S11 | S12

1968

Accessories Found

18" X 5 FT FIR SWAG 576°E 29.8 FT (REC
574°E 43 LKS)

28" Hemlock 536'20"W 57.0 FT (REC 86 LKS)

CORNER OF SEC. 1 & 2 ONLY BEARS
N89°23'E 199.2 (BLM RECORD)

New Accessories

8" FIRE 582°W 27.0 FT Scribed X BT
ON DOUBLE BLAZE 3 1/2" MAG NAIL
RIGHT SIDE CENTER

8" FIRE 542°W 12.2 FT Scribed X BT
ON DOUBLE BLAZE 3 1/2" MAG NAIL RIGHT
SIDE CENTER

Sketch of Monument, Accessories, and General Area

Location & Comments

MON IS ON A BENCH ABOVE
CUTBANK 45 FT EAST OF
LOGGING ROAD

MAP GIS LOCATION

43° 33' 09" N
123° 60' 42" W

Comp. Decline 14 1/4° E
Agency DCSO
Party Chief J. Corum
Note keeper
Witnesses STRAUSE

CS 67/62-36 pg 2/3

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald A. Quimby

OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

3-31-26

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Closing corner Secs 11 & 12 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - Brass Cap at Cor. mkd: County Surveyors T26S R8W
 Office, 1968 CC S 11 | S 12
 New BTs- 15" Hemlock S.46°E. 30.0 ft mkd T26S R8W S11 CC CSBT
 11" Hemlock S.4°W. 36.3 ft mkd T26S R8W S12 CC CS BT
 This corner lies 150 ft. west of Sec. Cor. Secs. 1 & 2 (Rec. 148.5).

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15218-9)

The orig. closing cor. of secs. 11 & 12, on the S bdy. of secs. 2, perpetuated & recorded by Tracy, in 1968, monumented with an iron post, 1 1/2" dia., firmly set, protruding 12" above ground, with brass cap (properly) mkd.

from which the remains of the original BTs ²⁹⁸
 15 FT - A fir snag, 26" dia., bears S ^{74°E} 43 lks. with scribe marks T26S R12 BT visible on weathered bark blaze.

~~GONE~~ - A sawed hemlock stump, 15" dia., bears S.63°W., 29 lks. with scribe marks T26S R8W S11 visible on opened blaze. and bearing trees mkd. by Tracy

~~GONE~~ - A hemlock, 13" dia., bears S.46°E., 46 lks. with scribe marks T26S R8W S12 CC CS BT visible on open blaze.

~~GONE~~ - A sawed hemlock stump, 11" dia. bears S.4°W., 56 lks with scribe marks T26S R8W S11 CC CSBT visible on open blaze and a new bearing tree

28" - A hemlock, 9" dia., bears S.36 1/2°W., ⁵⁷⁰ 86 lks., mkd. T26S R8W S11 CC BT.

From this point the cor. of secs. 1 & 2 only, bears N.89°23'E., 2.26 chs. ¹⁴⁹¹⁶

Fd. & used on BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1128 surveyed Jan. 1983- (DCSO records Vol. 43 Page(s) 16755)

NEW -
 - 8" FIR, SCRIBED "X" "BT" ON DBL BLAZE
 BEARS, S 82° W, 27⁰

- 8" FIR, SCRIBED "X" "BT" ON DBL BLAZE
 BEARS, S 42° W, 12²

NEW TREES SPIKED RS CENTER 3 1/2" MAG NATLS

CORNER FALLS ON A BENCH ABOVE CUT BANK

DEC - 14 1/4²

45 FT EAST OF LOGGING ROAD

CS 67102-36 #9313

MAP LAT + LONG
 43.33090° N
 123.60462° W

B" X5 FT

6 INCHES