

GOVERNMENT CORNER RESTORATION FORM

FILED

TOWNSHIP 255 RANGE 8W SEC. 27 PLSS # 440200

Date: 4/8/20 By: ke
This survey consists of:

DOUGLAS COUNTY OREGON

DATE 4-1-24

Map: _____
Narrative: _____
Corner Rpt: CS 67162-38

Corner Designation 1/4 cor 27/34

DOUGLAS COUNTY SURVEYOR

Monument(s) Found: (Condition and Source)

2 1/2" DCSO BRASS CAP
proj 8"

- Condition report
- Not Found
- Renewed
- Unrecorded
- Surveyed In

Previous Renewals

DCSO 1968 CS 54/72-6

MONUMENT DETAIL
COUNTY SURVEYORS
OFFICE
T255 RBW

1/4 527
534
1968

Accessories Found

SAWN Singed 17" x 2 FT Hemlock Stump
S34°W 24.1 FT BLAZE SCNR FACE INSIDE
Add 3 1/2" MAG Nail TOP CENTER

RENEWAL

Monument Set (Procedure and Description)

MONUMENT DETAIL

New Accessories

13" X 1 1/2 FT Hemlock Stump N 32° E 13.0 FT

18" X 1 1/2 FT Hemlock Stump N 87° E 24.0 FT

36" X 3 FT Hemlock Stump N 78° W 12.5 FT

All 3 stumps have 3 1/2" mag nails
Set Top Center (B&D to mag nail = C.R.C.)

Sketch of Monument, Accessories, and General Area

Location & Comments

MON IS IN southerly end
OF LARGE recent clearcut

MON IS approx
25' SOUTH OF
GRAVE ROAD

Trimble GEB XT position

43° 35967685 N

123° 63483533 W

Comp. Decline. 14' 14" E
Agency DCSO
Party Chief S. RAHISE
Note keeper
Witnesses J. LORSUNG

CS 67162-38 pg 2/3

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
JULY 14, 1978
RONALD A. QUIMBY
1654

EXPIRES: 12/31/2026

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
 Alias _____ Description TRIMBLE GEO XT POSITION
 Alias _____ Description _____
 Alias _____ Description 43.35967685°N
123.63483533°W

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3949)

Set cedar 1/4 post 3 ft. long & 3" sq. from which a Hemlock, 20" dia., bears N.70°E., 25 lks. Hemlock, 10" dia., bears S.30°E., 14 lks.

DECLINATION 14 1/4°E RENEWED 4/1/26

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1968 - C.S. File 54/72-6

NO EVIDENCE Found ~~Orig. 20" now 32" Hemlock, alive, N.70°E., 16.5 ft. previously opened, shows scribe "1/4".~~

NO EVIDENCE - Orig. ~~10" now 13" Hemlock, badly decayed remains of stump, S.30°E., 9.2 ft., open & find reverse "BT"~~

Set - Brass cap at cor mkd: COUNTY SURVEYORS T25S R8W OFFICE 1968 1/4 S 27 S 34

NO EVIDENCE New BTs - ~~14" Hemlock N.10°W., 19.3 ft., mkd: "1/4 S27 CS BT"~~

17" x 2 FT TALL ~~8" Hemlock S.34°W., 24.1 ft., mkd: "1/4 S34 CS BT"~~
 This corner lies on moderate northerly slope, about 150 ft. E of small ravine, course N.

SINGED SAWN SOLID STUMP

✓ 2 1/2" B.C. 1/4" PROT 8" 1/4" BLAZE SCAR FACE INSIDE 120 ADD 3 1/2" MAG NAIL TOP CENTER

NEW REFERENCES:

THREE SAWN, SINGED, SOLID HEMLOCK STUMPS WITH A 3 1/2" MAG NAIL SET TOP CENTER (B&D TO MAG NAIL = C.R.C.)

A 13" x 1 1/2 FT. TALL STUMP; BEARS N 32° E, 13° FT. DISTANT

A 18" x 1 1/2 FT. TALL STUMP; BEARS N 87° E, 24° FT. DISTANT

A 36" x 3 FT. TALL STUMP; BEARS N 78° W, 12 1/2 FT. DISTANT

MONUMENT IS IN SOUTHERLY END OF A VERY LARGE RECENT CLEARCUT, AND IS APPROX. 85 FT SOUTH OF A GRAVEL ROAD.

CS 67/62-38 9/3/13