

DOUGLAS COUNTY SURVEYOR'S OFFICE

Designation: R-090 Station: R 749 T 27 S R 6 W S 24 1/4 D


Date Set: 1987

Set by (Agency): NGS

Date Recovered: 8/2000

Recovered by: DCSO

- | | | |
|---|-------------------------------------|------------------------------------|
| <input checked="" type="checkbox"/> Found | <input type="checkbox"/> New | <input type="checkbox"/> Reset |
| <input type="checkbox"/> Not Found | <input type="checkbox"/> Referenced | <input type="checkbox"/> Destroyed |



VERTICAL CONTROL

NGVD 29 Elevation: 469.04 Feet

Precision: 3rd

NAVD 88 Elevation: 144.021 Meters

Precision: 1st CLII

File # 08 66/38

Agency: DCSO

File # _____

Agency: NGS

Project: _____ Date: 2000

Project: _____ Date: 1991

HORIZONTAL CONTROL - south zone

N _____	E _____	Datum/Adj.: <u>27</u>	Precision: _____
Lat: <u>43 12 19.0</u>	Long: <u>123 21 05.5</u>	Agency: <u>DCSO</u>	File # <u>66/38</u> Date: <u>2000</u>
N _____	E _____	Datum/Adj.: <u>83</u>	Precision: _____
Lat: <u>43 12 18.5</u>	Long: <u>123 21 09.8</u>	Agency: <u>DCSO</u>	File # <u>66/38</u> Date: <u>2000</u>
N _____	E _____	Datum/Adj.: _____	Precision: _____
Lat: _____	Long: _____	Agency: _____	File # _____ Date: _____
N _____	E _____	Datum/Adj.: _____	Precision: _____
Lat: _____	Long: _____	Agency: _____	File # _____ Date: _____

DESCRIPTION AND TO REACH

Found: A 9/16 inch diameter stainless steel rod set under a 6 - 5/8 inch diameter aluminum collar and access cover set in concrete and flush with ground. Rim of access cover collar is stamped "R 749 1987"

To reach: At the intersection of southeast Spring Ave. and Short St. in Roseburg, Oregon T27S R6W Sec24

