

Weston-Dyker Book Mfg. Co. Portland, Or. - 25211

Aug 28 - 1893
T. 27 S. R. 6 W.

Beginning at corner to Sects 33 & 34. T. 27 S. R. 6 W.
N. M. Oregon Set post marked S. 33. T. 27 S. R. 6 W. on
on N. W. face and S. 34. T. 27 S. R. 6 W. on N. E. face
One of the Original Witness trees standing but
marks nearly obliterated and the other witness tree
has been destroyed I made new bearing trees to wit:
An Oak 20 in dia bears N 76 1/2° E. 300 links marked T. 27 S. R.
6 W. S. 34. C. S. B.T.

N Oak 16 in dia bears N 56° W. 556 links marked T. 27 S. R. 5 W.
S 33. C. S. B.T. - Var 19 1/2° E

Thence East 8.45 ch Set post for standard sec
3 & 4. T. 28 S. R. 6 W. The Original Witness tree gone
or destroyed. reestablished new post marked as per
instructions - from which -

N Oak 20 in dia bears S 5 1/2° E. 47 links marked as per
instructions

N Oak 6 in dia bears S 5 1/2° W. 70 links marked as per instructions
E. B. Walker & Ed Hickerson sworn chainmen

Thence East 40.00 ch Set post for 1/4 S cor the original
bearing trees destroyed. established new bearing
tree to wit:

N Oak 6 in dia bears N 63 1/2° W. 290 links

Myrtle 10 " " " N 54° E. 131 " marked as per
instructions - Var 21° E.

Continued on same course at 41.00 ch (Var 22° E.

at 43.25 ch left bank of South Umpqua river

at 47.65 ch right " " " " "

at 48.45 ch Set post for 1/4 S cor for sec 3 the
Original bearing trees washed out by river
Set new corner - from which

B Oak 6 in dia bears S 41° E. 312 links - No other tree near

Thence from sec corner to 3 & 4. - Var 19 1/2° E.

South 38.95 ch to 1/4 S. corner still standing

" 78.95 ch to sec cor of 3, 4, 9 & 10 set post as per
original B.T. standing -