County Surveyor's Record, Douglas County, Oregon

Survey No. 12

Made for D Cheshlin & Bro

Sept 24.
T.29S. R.3W.

Begin at Cor 22.23.26&27. T29°S R 3 W. — Bar 19½ E,
Thence East on blazed line 160.00 ch intersect at cor
to Sec 24&25 on Township line 2&3 W.
Thence North on township line 100.00 chains Set post
from which Thence East 20.00 ch Set post from which
Fir 18 in dia bears East 20 lks. Fir 10 in dia bears S 75° W 30 lks dis,
which is N.E. Cor of S.W ¼ of S.W. ¼ of Sec 18 T29S.R. 2 W.

Sur No 13

Sept 30
T.30S. R4W

Caroline Bealman

Begin at N.E. Cor of Cl No 42. in T30 S;R. 4 W
from which original B.T. bears
B Oak 36 in dia bears N 60° W 100 links dis,
Thence offset South 2.88 ch. to avoid S Umpqua River
Thence West 10.00 ch corner on Left bank of River
the original B.T. has been destroyed by floods.
I made a new corner by setting a ~~Stone~~ post 4 in Oak
square 3½ feet in ground, Scribed C 42 C.S, from which
A Maple 16 in dia bears S 62° E. 35 links dist

Cor

Sur No 14

Nov 8
T.30S. R.5W

L.M Puckett

Begin at a point 2.00 chains East of N.W. corner
of Jackson Reynolds D.L.C. No ~~59~~ 58 in T 30 S R 6 W,
Bar 19½ E,
Thence South 6.17 ch. Thence West 4.35 ch.
Thence S 28° E. 4.46 ch. Thence S 34° E, 8.58 ch
Thence N 76° E. 2.87 ch. Thence N 8° W. 9.50 ch,
Thence N 80¾ E 3.16 ch Thence N 8° W. 5.68 ch, to
Thence West 6.32 ch to place of begin. Cont 9.90 acres
Thence I commenced at a point 6.32 chains East
and S 8° E. 5.68 ch. from the N.W. Cor of Cl No 54
Set Fir post Scribed C.S.- from which W Oak 10 in dia S 70° W 52
Thence S 80°¾ W. 3.16 ch Set post from which
B Oak 12 in dia bears N 22° E. 29 lks. Thence S 8° E. 9.50 ch
to County Road leading from Canonville to Persius
Set post ~~fence~~ post Scribed C.S.- from which W Oak 14 in dia