

County Surveyor's Record, Douglas County, Oregon

Survey No. ....

Made for James Stuart

Sept 25 - 1902  
Tp 31 S., R 2 W.

Chairman; Chas. Patterson and Joe Reville, duly sworn.  
From Sec. corner to 10, 11, 14 and 15 run South (var 20° E)  
40.30 chs. quarter corner. Thence South 20.15 chs. set post for quarter quarter  
corner from which a fir 16" in diameter bears West 5 links, Thence West  
39.17 chs. set post marked C.S. from which a pine 20" in diameter bears  
S 18° 30' W. 52 links. Thence North 20. chs intersect at quarter corner between  
secs. 10 and 15.

C. E. Roberts Co. Surveyor

Sept 27 1902  
Tp 30 S. R 2 W

Made for Jas. Richards

Chairman C. P. Thomas and A. F. Hammsley, sworn.  
From Sec. corner to 27, 28, 33 and 34 West (var 20° 30' E) 39.65 to  
quarter corner between S. 28 and 33, Thence West 19.82 1/2 chs., Thence North  
20. chs. set <sup>post for</sup> quarter quarter corner from which a fir 8" in diameter bears East  
12 links, Thence East 39.17 chs. set post for quarter quarter corner from which  
a fir 30" in diameter bears S 45° E. 5 links, Thence South 40. chs. set post  
for quarter quarter corner from which a fir 28" in diameter bears N 63° E 38 links  
Thence West 39.17 chs. set post for quarter quarter corner from which a fir 7" in dia  
bears North 30° E. 10 links

C. E. Roberts Co. Surveyor

Sp 30 S., R. 30 W.  
Sept. 30. 1902.

Made for L. L. Pender

J. F. Preble and J. Baltzer chairmen, sworn.  
From North-East corner of of Sec. 25 run West (var. 20° 30' E)  
at 40.20 chs. intersect 40 links South of quarter post between Secs 24 and 25  
Thence S. 89° 42' E. on true line between 24 and 25 20.10 chs. set post  
for quarter quarter corner from which a black oak 12" in diameter bears S. 16° W. 18 links  
Thence South 9.95 chs. to right bank of South Umpqua river.

C. E. Roberts Co. Surveyor