

County Surveyor's Record, Douglas County, Oregon

Survey No.

Made for

Corner No 7 I reestablished cor. for Secs. 16, 17, 20 & 21
 Set white oak post 5" x 5" x 3' from which
 Red fir 14" dia brs N 62° 25' E 38 lbs dist.
 B oak 6" " " S 33 42' E 35 " "
 " " 14" " " S 38 00 W 17 " "
 B oak 16" " " N 36 00 W 35 " " This is old Gov. tree
 and is plainly marked and in good condition.

Corner No 8 I took for position of this corner a point from
 which the old witness trees as made by Britt brs as follows
 Red cedar 16 in dia brs S 70° 20' W 22 lbs dist.
 " " 24 " " " N 65° 40' E 44 " "

Corner No 9. Corner set by C. C. Roberts. In good
 condition and old trees standing.

M. B. Gerrmond

Sept 21 1908

Dep. Co. Surveyor

Survey made for Herbert Conville to
 find the approximate location of the North-West
 1/4 of sec. 16 T 26 S. R 3 W.

Began survey at a point 40.00 chs North of the
 south-west corner of sec. 16. From this point ran
 random East 40.00 chs, and set temporary stake. From
 this temporary stake ran random line North at
 38.80 chs fell 10 lbs west of 1/4 corner on the north side
 sec 16. I reset this 1/4 corner with durable white
 oak post 4" x 4" x 3' properly marked and note that
 old B Ts are still standing as per Gov. field notes

M. B. Gerrmond

Dep. Co. Sur.