

County Surveyor's Record, Douglas County, Oregon

Survey No.

Made for *Douglas Waite* and *W.H. Rose*

Reston-Bryant Book Mfg. Co., Portland, Or. - 88444

T. 27 S. R. 4 W.

Purpose of survey to mark the line between S.E.⁴ of S.W.⁴ and S.W.⁴ of S.W.⁴ Sec. 14 and the line from N.W. cor. of N.E.⁴ of N.W.⁴ of Sec. 23 in T. 27 S. R. 4 W. to S.E. cor. of N.E.⁴ of N.W.⁴ of Sec. 23.

I begin at stake set for N.W. cor. of S.E.⁴ of S.W.⁴ of Sec. 14 T. 27 S. R. 4 W. (established by C.E. Roberts, Co. Surveyor Jan 12-14, 1904) from which a cedar 6" diam bears N. 15° W 70 lks + a cedar 10" diam S 35° W 76 lks. Thence I run S. 0° 45' W (Variation 21° East) on random between S.E.⁴ of S.W.⁴ and S.W.⁴ of S.W.⁴ of Sec. 14, at 20.22 chains intersect Sec. line between Sect 14 + 23, - 50 lks West of S.W. cor. of S.E.⁴ of S.W.⁴ of Sec. 14 which is an oak stake (set by C.E. Roberts Co. Surveyor Jan 12-14, 1904) from which a B. Oak 24" bears S. 41° E. 144 lks. Thence I run N. 0° 40' W. on true line bet S.E.⁴ of S.W.⁴ and S.W.⁴ of S.W.⁴ of Sec. 14 at 20.21 chains intersect NW cor. of S.E.⁴ of S.W.⁴ of Sec. 14.

Begin at NW cor. of N.E.⁴ of N.W.⁴ of Sec. 23 T. 27 S. R. 4 W. thence S 45° E on random at 28.63 chains intersect E. line of N.E.⁴ of N.W.⁴ of Sec. 23, 25 lks north of S.E. cor. of N.E.⁴ of N.W.⁴ of Sec. 23 (which is a stake set by C.E. Roberts, Deputy Co. Surveyor, Dec 1912).

Thence N. 45° 20' W on true line 28.79 chains intersect at corner.

C. Boyer
Deputy Co. Surveyor

Nolan Rose
Douglas Waite } Chainmen

Surveyed Jan 24th 1913.
Recorded " 27 " 1913.