

Survey No. ....

Made for *A. G. Dunlop*

T. 28 S. R. 4 W. Survey to establish corners and boundaries of Lots 3, 5, 6 and S. E. <sup>4</sup> of N. W. <sup>4</sup> of Section 6, T. 28 S. R. 4 W.

See Survey for L. Hatfield pp. 174-5-6.

Begin at post established for center of Sec 6.

N. 89° 20' W. On East and West center line of Sec 6.

20.00 1/16 Sec. cor. set a post 4x4x36, marked C S 1/16 S from which a Red Fir, 10" diam. marked C S 1/16 S B T bears S 6 1/2° W. 4 links and a Pine 24" diam. marked C S 1/16 S B T bears N. 77 1/4° E. 37 lks.

South On random North and South center line of the S. W. <sup>4</sup> of Sec 6.

39.86 Intersect South line of Sec 6, 13 lks West of 1/16 Sec post.

N. 0° 11' W. On true North and South center line of S. W. <sup>4</sup> of Sec 6.

39.86 To 1/16 Sec post in North boundary of S. W. <sup>4</sup> of Sec 6. Set stakes at 5.00 chain intervals.

Begin at post established for 1/4 Sec cor post in West boundary of Sec 6.

South On West boundary of Sec 6

40.02 Intersect South boundary of Sec 6, 4 links East of post for cor. of Sections 6-7-1-12.

N. 0° 03' E. on true West line of Sec 6.

20.01 1/16 Sec. cor. marked with a Maple 8" diam, C S 1/16 S. for corner from which a Red Fir 12" diam, marked C S 1/16 S B T bears N. 35 1/4° E 27 links and a White Fir, 12" diam, marked C S 1/16 S B T bears N. 62° W. 58 links.

40.02 To 1/4 Sec corner.

June 23<sup>d</sup>, 1913.

Begin at Maple 8" diam established for 1/16 Sec corner in West boundary of S. W. <sup>4</sup> of Sec 6.

S 89° 45' E On random East and West center line of S. W. <sup>4</sup> of Sec 6.