

County Surveyor's Record, Douglas County, Oregon

Survey No.

Made for.

by C. C. Roberts,

I set a stake 59 lks South of said rock from which stake I mark.

A. B. O. 18 in $N. 11^{\circ} 45' W.$ 196 lks.

" " " 9 " $N. 43^{\circ} E$ 369 "

Thence East

1996

I set a ^{Rock} 7x7x10 inches with pieces of broken cast iron binder frame. 6 inches below the surface of the ground. and for the S.W. corner of the John Cox claim No 49. from which

A. B. O. 28 in bearing $N. 44^{\circ} W.$ 45 lks.

" " " 36 " " $S. 68^{\circ} E.$ 141 "

From the corner set for S.W. Cor C 49 I ran

East, 36.54 and set a rock 8x8x8 inches with a spike above the rock 6 inches below the surface, as the S.W. corner of Burnells one acre tract.

40,27 Set, a Sandstone rock. 6x8x12 inches below the surface, for Burnells S.E. corner. from which

A. B. O. 20 in bearing $N. 38^{\circ} 15' W.$ 128 lks.

It runs out Fry's land I began at the rock called for in Fry's deed, in the center of Co road on the west line of C 49, but which is 7 lks west of claim line.

Thence $S. 72^{\circ} 56' E.$ 24.15 to the angle in the Co road

Thence $S. 87^{\circ} 59' E$ 18.43 to a rock at the junction of the county road. Thence $S. 45^{\circ} W.$ 15 chs to the present fence on Fry's South boundary.

Thence $N. 89^{\circ} 59' W.$ 20.60 to the angle in Fry's South boundary. thence $N. 72^{\circ} 56' W.$ 21.64 chains to the west boundary of C 49. Set a rock 8x8x10 inches and mark

A. B. O. 24 in $N. 20^{\circ} E.$ 67 lks.