

County Surveyor's Record, Douglas County, Oregon

Survey No.

Made for *W. G. Lawrence*

June 1, 1915

19.49

Begin at center of Section 5 and run S 89° 33' E
 Set subdivisional Corner a Yew post 4"x4"x3 1/2"
 marked C.A. 1/16 A from which
 A fir 22" marked C.A. 1/16 A br S 69° 25' E 47 lbs.
 " " 32 " " C.A. 1/16 " " N 57° 30' W 31 "
 From this corner, post set on my previous Survey
 br North 88 1/2 lbs and East 76 lbs - a post set by Briggs
 " " " " " " 129 "

Beginning at a point N 70° 04' W 27.14 Ch. from 1/4 post
 bet Sections 5 and 8.

Thence N 89° 37' E 11.00 at 11.25 falls 24 lbs N of a post)
 S 23° 35' E .90 Ch. set by unknown person

East 8.39 Chs. Corner of fence N 22 lbs and E 33 lbs

N 10° 08' W 12.51 To Subdivision Corner.

N 89° 33' W 19.49

S 0° 04' E 12.39 To Beginning

Var 20° 20' E

19.875

Sep 8th 1915

From Center of Section 5 N 89° 33' W
 Set subdivisional Corner a fir post marked C.A.
 1/16 A from which a fir 12" mld. C.A. 1/16 A br S 48° 20' E 36 lbs
 " " " " " " " " N 43° E 31 "

From the post East 8.39 Chs Set subdivisional
 Corner a Cedar post 4"x4"x3 1/2" from which

A fir 24" in dia mld 1/16 A C.A. B J br. S 13 1/2° W 27 1/2 lbs

" " 26 " " " " " " " " N 71 1/4° E 41 3/8 "

From above point Fence br 35 lbs East and
 21 1/2 lbs North.

Recorded for Frank. Cain
 by J. W. Cole
 Deputy.