

County Surveyor's Record, Douglas County, Oregon

Survey No.

Made for

West 40.82 S 89° 50 E 20.41	<p>From 1/16 Cor. bet. NW⁴ and NE⁴ Sec 332. on Random Intersect Top line 10 lks South of 1/16 Corner On true line Set 1/16 Cor from which A fir 12" in dia. br. S 0° 06 E 19 lks " " 6 " " " N 74° W 28 "</p> <p>Set 1/16 Cor. Made NE⁴ Sec 31, 20, 21 West of Cor. Secs. 29-30-31-32.</p>
S 0° 16 E. 20.15	<p>Intersect 1/16 Cor. set by Thiel From Cor. of Secs. 29-30-31-32 on random</p>
North x 40.08	<p>Intersect 45 lks. West of 2^d Cor. bet. 29-330 Renew corner from remains of original trees Mark A Cedar 8 in dia. br. N 62 1/2° W 77 lks " " 40 " " " N 81 1/2° E 102 "</p>
S 0° 38 W 20.04	<p>on true line Set 1/16 Cor A fir 10 in dia br. N 23 1/2° E 30 lks " " 9 " " " S 8 1/2° E 9 "</p>
West 40.00	<p>on random Set Temp. Corner. From 1/4 Cor. bet. Secs. 30 & 31.</p>
North 19.90 20.00	<p>Intersect 1/16 line run from East Set stake for temp cor. accepted by Thomas and Goldabrin (see Field Book 13 page 23 for signature) #39 1/2 newer filing system</p>