

County Surveyor's Record, Douglas County, Oregon

Survey No. ....

Made for .....

T 23 S, R 7 W.

Set post 4"x4"x3' for 1/4 cor. n bdy sec. 6 from which  
W oak 16" dia hrs. S 7° 00' W 120 lbs dist Old marks in  
L " " 8 " " " S 20 05 E 197 " " evidence - B.Ts.

T-22 S, R 7 W.

set S. Stone 4"x10"x24" for cor of Secs 31 & 32 on Stand. Parallel  
W. Oak 12" dia hrs N 39° 56' W 240 lbs dist. All old land marks  
" " 15 " " N 14° 00' E 378 " " show new corner is  
L Cor set on true line by prop. measurements. correctly placed

T 27 S, R 4 W

Set S. Stone 8"x10"x26" for S.E. Ext. L cor of the J. Matthew D.P.C. 42  
W. Oak 8" dia hrs N 32° 25' W 87 lbs. dist. Old B.Ts. in evidence  
R Cedar 22 " " N 34° 45' E 74 " "

Set oak stake 4"x4"x3' for N.W. Cor of above claim  
B. Oak. 26" dia. hrs. N 79° W 50 lbs dist. Old B.Ts in evidence  
" " 30 " " S 59° 45' W 60 " "

T 27 S, R 6 W

S. Stone found, <sup>set</sup> for 1/4 cor. on W. bdy sec 6.  
Old bearing tree standing on S.W. (for cor. notes)  
I mark W. O. <sup>7" dia</sup> for other tree which hrs N 83° 58' W 822 ft. dist

T 25-S, R 6 W

CC - 20 - 2001, Pg 180  
? JMB

Set S. Stone 5"x5"x15" for 1/4 cor. on S side of sec. 32 (This should no doubt be  
Sec 5 = 1/4 Cor bet Sec 5, 6, 7, 8  
" 32, 31)  
Alder 20" dia hrs S 50° 20' W 75 lbs dist. Iron B.T. was gone. Old mark  
L W. Oak " " N 65 45 E 115 " " was found set <sup>by</sup> previous

T 25 S R 6 W

Set S. Stone for 1/4 cor. on W. bdy of sec 5  
R. fir 14" dia hrs N 46° 40' W 77 lbs dist. Old B.T. in evidence  
L " " 34" " " N 47 20 E 39 " "

T 25 S, R 6 W.

W. Oak post 4"x4"x3' for cor. of Secs 26, 718 from which  
R. fir 8" dia hrs. N 49° 40' E 31 lbs dist  
L W. Oak 6 " " N 23 45 W 48 " " Old B.T. in evidence  
R fir 5 " " S 53 40 E 4 " "  
R " 5 " " S 28 20 W 25 " "