

## County Surveyor's Record, Douglas County, Oregon

Survey No. ....

Made for .....

✓  
T 25 S, R 6 W

Set W. oak post 4" x 4" x 3 for 1/4 cor bet. <sup>secs,</sup> 7 & 8  
 R. fir. 8" dia bet. N 52° 00' E 11 lbs dist. Old B.T. in evidence  
 R " 50" " " N 60 00 W 27 " "

✓  
T 25 S, R 4 W

Set S. Stone 2 x 8" x 16 for 1/4 cor on East ldy sec. 8.  
 Old cor. B.T. to the S.E.  
 W. Oak 40" dia bet S 36° 30' W 53 lbs dist

✓  
T 26-27 S, R 4-5 W

Marked R. fir tree 15" dia for N.W. cor of T. 27-4 from which  
 R. fir 16" dia bet N 77° 30' W 33 1/2 lbs dist  
 R " 10 " " S 28° 00' E 47 " " Old B.T. in evidence  
 B Oak 12 " " N 77 30 E 82 " "  
 R fir 14 " " S 62 08 W 33 " "

Set patch post 5" sq for 1/4 cor on W side sec 31 above T 27-4  
 Note 1 Old B.T. standing

Set Broad stone 6" x 6" x 16" for 1/4 cor on E side sec 31 above T 27-4  
 W. Oak 7" bet. S 50° 30' W 14 lbs dist. Old B.T. found  
 B " 8" " S 40 48' E 108 " "

✓  
T 26 S, R 3 W.

Set S. Stone 4" x 6" x 18" for 1/4 cor on W side sec 21 from which  
 R. fir 15" dia bet N 62° 34' W 83 lbs dist Old B.T. found  
 " " 18" " " N 70° 56' E 109 " "

✓  
T 22 S, R 5 W

Set S. Stone 5" x 5" x 20" for 1/4 cor bet. Secs. 4 & 5  
 R. fir 8 dia bet N 28° 05' E 21 1/2 lbs dist Old B.T. still standing  
 " " 6 " " S 19.20 W 22 1/2 " "

✓  
T 21 S, R 5 W

Set S. Stone. 4 x 5 x 16 for 1/4 cor bet Secs 20 & 31  
 G. Woods 16" dia bet N 44 1/2 W 30 lbs dist Old B.T. found  
 " " " 5 " " S 72 1/2 E 57 " "