

County Surveyor's Record, Douglas County, Oregon

Survey No.

Made for.....

✓ T 23 S, R 4 W

Cor. for secs. 10, 11, 14 & 15 & reset with granite stone 6"x8"x14" and note that the S.W. cor. Nit. tree and the N.E. cor. Nit. tree are still standing

✓ T 22 S, R 8 W

Set cedar stake 5" sq for 1/4 cor. bet. secs 14 & 15
Old cor. bearing trees still standing

✓ T 22 S, R 8 W

Set S. Stone 6x8x12 for N.W. Cor sec 14
Old cor. bearing trees still standing

✓ T 22 S, R 8 W

Set fir stake 4" sq for 1/4 cor north side sec. 14 from which
A fir 20" dia has N 66° 20' E 19 1/2 lbs - old cor B.T. found
W " 16" " " S 9 30 W 77 " "

✓ T 26 S R 6 W

L. Cor. C 13 38 and 62
Set Sandstone 4"x4"x13" marked 38 on west and 62 on East side
A. W. Oak 20" marked C.S. C. 62, T. 26 S. R. 6 W. bears S. 30° E 60 links

" " " " "

S.E. Cor C 162 Sandstone 4"x4"x20" marked X 62. from which;
A. B. Oak 20" marked C.S. C. 62, T 26 S. R. 6 W. B.T. bears N. 14° E 164 links

" " " " "

Meander post bet. Sec's 5 and 6 Set Sandstone 3"x18"x20"
on left bank of River. No trees near

Note - The above corners were established by original B.T.'s
which I found standing, but girdled and dead

Dec 8th. 1914 Frank Cain
Co. Surveyor.

✓ T 29 S R 6 W

S.W. Cor A.D. Willis DLC, N° 45
A. Fir 48" in dia, marked X C. 45 bears S. 70° W: 11 1/2 lks.

" " ✓

S.E. Cor A.D. Willis DLC N° 45.

" " ✓

A Maple 14" in dia marked C. 45, C.S. T 29 S R 6 W bears S. 20° W, 8 1/2 lks
" " 16 " " " " " " " " N. 70° W. 72 "

Interior L. Cor. same claim,

A. Fir 12" " " " " " " " " S. 15° W. 49 1/2 lks

" " 30" " " " " " " " " N. 15° W. 34 1/2 lks