Pg. 270

Pg. 270

County Surveyor's Record, Douglas County, Oregon

Survey No. .....

Made for Survey for M J Riggs

T 24 S R 6 W
June 9 1915
? (Chain)
M J Riggs
F. Adams
(Field Bk 18=37
Page 48)
S 89°40 W
120.02

Survey made Sec line bet Secs 23-26 and East boundary of W half of NW¼ of Sec 26.

Begins at Cor to Secs 23-24-25 & 26 Find cor previously set N 50° E 17 li from correct place for corner, as determined from both Witness trees which are standing

On random line Solar bearing

Intersect 12 li N of ¼ Cor. Tree S 18½° W Standing Tree N 18° E is down. Renew Cor with Cedar post from which I mark A B Oak 16 S 32° ¾ E 59 li
" " " 24 N 87° W 43 "
" Fir 36 S 42½° W 77 "

From a fence post which G. W. Cooper testifies is the location of ¼ Cor bet Secs 22-23, established from stump of original BT S 16½° E 292 li, by M B Germond.

South 39.39

On random

Intersect Random E & W line 80.27 Ch. West of Cor of Secs 23, 24, 25, & 26

80.35

Intersect ¼ Cor. bet 27 & 26 Renew Cor from original trees Find Laurel standing and chop out marks on stump of Oak Set Rock mkd + 6 x 14 x 16

mark A B Oak 12 S 3° W 143 li

Set a Rock 8 x 16 x 20 for Cor to Secs 22, 23-26 & 27. 27 lks South of transit line E and W cor Transit line N & S, mark An ash 14 N 17° E 203 li
" " 9 N 5° W 240 "
" " 10 S 82½ E 134 "
Maple 20 S 20½ W 424 "

Set 1/16 Cor N 89°46 E of Sec Cor 22, 23, 26, 27 20.10 Ch.
A Rock 14 x 14 x 30 and mark
An Ash 16 in dia East 166 li
" " 12 " " N 85¼° W 292 "

Set a Rock 6 x 8 x 12 for ¼ Cor (bet 23 & 26)
marked + No trees near