

County Surveyor's Record, Douglas County, Oregon

Survey No. ....

Made for W. J. McElhinny

5.89°-55'E

20.10 ch.

On E. & W.  $\frac{1}{2}$  of Sec. 31

$\frac{1}{16}$  Sec. Cor. Set Post 3"x3"x36" marked  $\frac{1}{16}$  S. C. S. from which  
a W. Oak 20" marked C.S.B.T. - N. 56°-35'E. - 166 Lks.  
a W. " 16" " " " 5.74°-05'E. - 228 Links.

40.20 ch

To  $\frac{1}{4}$  Sec. Cor. in E. Bdy of Sec. 31

N. 0°-10'E.

40.26 ch

Begin at the D.W. Cor of the D. E.  $\frac{1}{4}$  of S. E.  $\frac{1}{4}$  of Sec. 31  
On W. Line of E.  $\frac{1}{2}$  of S. E.  $\frac{1}{4}$  of Sec. 31  
Intersect at N.W. Cor. of E.  $\frac{1}{2}$  of S. E.  $\frac{1}{4}$  of Sec. 31

North

20.22 ch

Begin at S. E. Cor. of Sec. 31, which I re-establish  
in its original position from original B.T.s  
Between Secs 31 and 32

$\frac{1}{16}$  Sec. Cor. set post 3"x3"x36" marked  $\frac{1}{16}$  S. C. S. from which  
a W. O. 8" dia. marked C.S.B.T. N. 55 $\frac{3}{4}$ ° W. - 167 $\frac{1}{2}$  Links  
a W. O. 10" " " " N. 44°-25'E. - 178 " "

40.44 ch.

Intersect at  $\frac{1}{4}$  Sec. Cor. between Secs 31 and 32 a rock in place

5.89°-57'W.

40.22 ch

Begin at  $\frac{1}{16}$  Sec. Cor. in E. bdy S. E.  $\frac{1}{4}$  of Sec. 31  
On random E. & W.  $\frac{1}{2}$  of S. E.  $\frac{1}{4}$  of Sec. 31  
Intersect W. Line of D. E.  $\frac{1}{4}$  of Sec. 31  
22 Links South of  $\frac{1}{16}$  Sec. Cor..

5.89°-47'E.

20.12 ch.

On True line

Intersect N. & S.  $\frac{1}{2}$  of D. E.  $\frac{1}{4}$  of Sec. 31 - Set Post marked  
C.S.  $\frac{1}{16}$  S. from which a W. Oak 18" dia. marked C.S.B.T. (S. 68°E) 74 Lks.  
and a W. Oak 12" dia. marked C.S.B.T. (N. 29°-40'E.) 286 Lks.

20.18 ch.

N. 0°-10'E. from S.W. Cor. of S. E.  $\frac{1}{4}$  of S. E.  $\frac{1}{4}$  of Sec. 31

Note -  $\frac{1}{2}$  stands for Center Line

Surveyed By C. C. Boyer Dep. Co. Surveyor

Recorded By J. C. Fear - Apr. 10, 1919  
Dep. Co. Surveyor.