6

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No. 00 *Made on* Feb. 22,23,24, 1916	*Survey No.* *Made on*
In Town. 26 S. *Range* 4 W. *Sec.* 28	*In Town.* *Range* *Sec.*
Made for Joseph Thornton	*Made for*
Purpose of sur. was to est. the lines and cors of the N. "L" part of D.L.C.No.52 in sec. 28 above Tp & Rg. C.S 1/41 F.B. 74. Pg. 27-28	*Purpose of*

Feet	
	I began sur. by making a diligent search for the cors. to the Cl. and find them all destroyed and lost. Next, after several ran. lines run and diligent serch I locate the cor. of secs. 27,28,33 & 34. The large Ash "B.T" stump is still in evidence and the letters "B-T" discernible. I reest. this cor. with S.Stone 5" x 12" x 18". I start on ran. line, using needle, var. 21¼° E.
	West at
1320	I set in pt. 4 at
1361.5	I set in pt. 5 and offset N.00°-12' W. 76.4 ft. and cont. ran. line west, at
2623.5	I set in pt. 6 and made diligent search for ¼ cor. but could find nothing, at
3168.8	I set in pt. 7 on offset ran. line and make dil. search fot "B.T" to the S.W. cor. of Cl., but only found an old rotted stump. I set in temp. pt. Marked pt. "A" from this stump according to Gov. field notes. I then cont. off. ran. W.
5284. 8	I fell 19.0 ft. S. of sec. cor. for secs. 28,29,32 & 33. I reset this sec. cor. with a S.Stone 6"x 15"x 20" and note three old "B°T" still in evidence. Hence. I note true len. of sec. line bet. secs. 28 & 33 is 5284.8 ft. and true b'ring (from solar obsvr) is N. 88°-52' W. This sec. line gives me the south true/positions of the S.E & S.W.Corners I seek.
	I then begin sur. at the ¼ cor. bet. secs. 27 & 28. I find true position of this cor. and run a true line bet. it and the cor. to secs. 27,28,33 & 34. I find the Bearing of this line by needle to be S.01°-27' E. and 2713.7 ft. in len. At a pt. marked "B" on this true sec. line 1326.6 ft. Northerly /of above des. ignated sec.cor. I turned and run a ran.line
	West, and at
1327.9	I set in temp. pt. 9 for the N.W. cor. Cl. No. 49. Then I return to pt. 4 and set in true S.E. Cor. on the true sec. line by sighting on the cor. of secs. 27,28,33 & 34 turning lt. 91°-39' to pt. 9 and measuring along this line 23.8 ft.; and set in the true pt., which is a stake. Then I run on this line which has a bearing of N. 01°- 33' W.
1320.0	from the true S.E.Cor. and set in the true N.W.Cor. of Cl. No. 49. I then cont. this same line on (N. 01°- 33')
630.96	to the true N.E. Cor. of Cl. No. 52. From this cor. I run on a line accord to the calls of the old notes; and which has a bearing of N. 89°-48' W.
1811.0	to the true NW NE. Cor. of Cl. No. 52. From this cor. I turn and run Parallel to the East line, or S. 01°- 33' E.
1923.9	to the true sec. line and set in cor. for the true S.W.Cor. of Cl. No. 52.
	I note that this cor. is set in
1816,8	westerly on the sec. line from the Tr ue S.E. Cor. as above described.
	I call this closing good on account of the experience of the chainmen and the topography of the country through which the survey was made. And from the foregoing ran. and true lines I compute the bearings and distances of the lines around the piece of land as follows.-

(Cont. on P. #13