

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Field Book No. 1 and 20-44

V. 4/25

Survey No. Made on Jan. & Feb. 1917  
 In Town. 27 S. Range 6 W. Sec. 24.  
 Made for Oscar Lindsay  
 Purpose of was to find the lines of his real property that lies west of the City of Roseburg, Oregon. "HIGH ACRES FARM" ✓ R

Survey No. Made on  
 In Town. Range Sec.  
 Made for  
 Purpose of

Began survey on the U.S.G.S. meridian in the County Court Yard. I transferred this meridian across to Mt. Nebo and used it during the entire survey.

I carried the meridian to the S.E. Cor. of the John Lieser, D.L.C. No. 59 in above tp. and rg. I reest. this cor. as noted in the records, and run West.

- 7.17 chs. to the N.W. Cor. of the property and set in 1 1/2" x 24" iron bar. from which  
 A W. Oak 12" dia. brs. S. 03°-25' W. .9575 chs.  
 A R. Fir. 8" " " S. 74°-50' E. .2800 "  
 South
- 31.74 " to the S.W. Cor. of the property and set in 1 1/2" x 48" gal iron pipe.  
 A. B. Oak 14" in dia. brs. S. 21°- 30' E. .64 lks.  
 A. W. Oak 8 " in dia, " N. 84°- 55' E. .991 1/2 "  
 S. 89°--57' E.
- 13.70 " to 1" X 28" black iron pipe, cont. on line easterly
- 16.75 " to a hub, from which the cor. of secs. 19, 24, 25, & 30 brs. S. 70°-43' E.
- 25.24 " to a 1 1/2" x 48" gal. iron pipe.
- 33.72 " to a 1 1/2" x 50" " " " and the river bank. The point is witnessed by  
 An ash 13" in dia. brs. S. 72°- 39' E. . 63 chs.  
 A Maple 8" " " " N. 13°- 22' E. . 783 chs.  
 N. 11°- 25 1/2' W.
- 8.81 " to a 2" X 36" gal iron pipe.
- 14.61 " to a hub point, on river bank  
 N. 01°- 07' W.
- 5.46 " to a point on river bank  
 N. 12°-10' E.
- 3.195 " to a point on the river bank  
 N. 10°- 31' E.
- 3.945 " to a point on river bank  
 N. 40°- 51' E.
- 6.39 " to the N.E. Cor. of property and a 2" x 36" gal. iron pipe, from which  
 A forked W. Oak 12" in dia. brs S. 46°-07' W. .548 chs.  
 A B. Oak 15" " " " N. 86°-14' W .855 "  
 West.
- 15.10 " to an 1" x 30" iron bar.
- 29.10 " to the iron pipe and the place of beginning. In making this survey it was necessary to establish the true south half of the sec. line bet. secs. 23 and 24. This line was estab. and its true cen. pt. was found by double chaining.

Also, the true bearing of the line bet. secs. 24 and 25 was found, and from the true cen. pt. of the line bet secs. 23 & 24 as above mentioned a line was established parallel to the true line bet. 24 and 25. This true parallel line was run as the line through the true cen. of the SW 1/4 of sec. 24 and the true line bet. lots 4 & 5 which was needed and which is the true south bdy. of land surveyed. The work was well executed and all corners permanently established. The chaining was by M.B. Germond and F.C. Frear. The closing was considered good. The work was performed in bad weather and the lines are run over very rough and mountainous land. A complete map of the survey was made.  
 ( See file Envelope No. 4.) 25

M. B. Germond  
 Co. Surv.