

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No. *Made on* June 2nd. 1917
In Town. 30th. *Range* 6 *Sec.* 24
Made for S.J. Jones
Purpose of to determine property Lines.

Survey No. *Made on* Mar. 8th 1917
In Town. 25 S. *Range* # 7 *Sec.* 26
Made for Mrs. Jesse Thompson & H.P. Conn
Purpose of Deed description.

R ✓
 F. B. 6 = 73.

R ✓
 F. B. 1 = 69.

Began survey at a point called for in the deed description, which point is marked by a round iron rod $\frac{1}{2}$ " X 24" and is set on the South side of the O. & C. R.R. rt-of-way and in the center of a small stream. Also, said point is witnessed by an iron block that bears N.36° E. 15 lks. dist. Also said point is tied to the Iron Rod that marks the most^{northerly}/cor. of the town of Riddle as follows (deed description) "said iron rod bears S.20° W. 11.89 chs."

Thence around the piece or parcel of land as follows:-

S. 40°-04' E. 2.55 chs. along line of Hardman Est. to a $\frac{1}{2}$ " X 24" iron bolt; and fr. wh. a stone 3"X 5" X 14" brs. N. 42°-45' E. 20 lks dist.
 N. 42°-51 $\frac{1}{2}$ ' E. 9.88 chs. to a $\frac{1}{2}$ " X 20" iron bolt in cen. of Co. road
 N. 46°- 56' W. 3.69 " to a $\frac{1}{2}$ " X 24" " " and R.R. Rt- of -way.
 S. 36°- 00' W. 9.65 " to the place of beginning.

J. C. Fear

Began survey at a point on the N. side of the County road. Said point is called Sta. 0 and is 1-1/8 " X 16" iron bolt, from which a W. Oak 30" in dia. brs. S. 08°-00' W. 123.2 ft. Also, said begin. pt. bears N. 00°-38' W. 843.5 ft. dist. from the stone that marks the N.W. Cor. of the Alva Churchill D.L.C. No. 44 in Tp. 25 S., R. 7 W. Thence, around the piece of land as follows:-
 North 3682.2 ft. to the N.W. Cor. of tract which is marked by a large rock
 N. 58°-00' E. 61.2 ft.
 S. 84°-03' E. 95.7 ft.
 N. 87°-23' E. 219.2 ft.
 S. 85°-51' E. 222.4 ft.
 S. 84°-09' E. 167.0 ft. to the N.E. Cor. of tract, which is marked by $\frac{1}{2}$ " X 40" iron pipe, from which A B. Oak 18" dia. brs. N. 68°- 00' W. 13 ft., and
 A B. Oak 20" in dia. bears East 47 ft., thence,
 S. 00°-17' W. 3680.8 ft. to the S.E. Cor. of tract, which is marked by 4" X 8" X 15" stone, from which A B. Oak 40" in dia. brs. 03° 40' E. 60 lks., and
 A W. Oak 10" in dia. Brs. N. 20°-45' W. 167.0 ft. thence,
 S. 89°-50' W. 737.6 ft. to the beginning point.

Work well executed. Chaining very well done. Closing good.

J. C. Fear
 Dep. Co. Surveyor.