

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

25

| | | | |
|---|----------------------------------|-------------------|----------------|
| <i>Survey No.</i> | <i>Made on</i> June 10 July 1918 | <i>Survey No.</i> | <i>Made on</i> |
| <i>In Town.</i> 29 S | <i>Range</i> 4 West | <i>In Town</i> | <i>Range</i> |
| | <i>Sec.</i> 24 | | <i>Sec.</i> |
| <i>Made for</i> B. M. Goddard et al | | <i>Made for</i> | |
| <i>Purpose of</i> To establish corner lines between | <i>Purpose of</i> | | |
| the lands of B. M. Goddard and his neighbors | | | |
| Hugh Blackman Bates and James Hilliard | | | |
| <i>M. 1. 35</i> | <i>F. B. 14 = 45</i> | | |

Began survey on June the 10th at the corner common to secs 25 26 35 and 36 of above tp and range I find this corner plainly marked and estab from the four Madrone B T s as per Gov field notes The corner is now a 5" x 6 cedar stake.

From the above described cor I start N.00 11 W on a random line and at 40 00 ch I set in a temp stake and make diligent search for the old orig Gov. cor. I could find no evidence that any cor. had ever been set I then continue on my random line and at 80.00 " I set in temp cor and again make diligent search for the old Gov cor. to secs. 23 24 25 & 26 but could find no evidence that such corner had been set. I then continue my random line on the same bearing and at 88 30 I fall 12 56 chs west of the S W cor of sec 24 as estab by M B Germond Dep Co Sur in 1908 The record of such estab is in vol 2 page 147 of the Surveyors records

Then in order to again ascertain the position of the original S W Cor of sec 24 I go west into another section and begin the survey at the N W Cor of the B L Stephen s Cl # 38 I identify the position of this cor from the testimony of D Dyer and note that the same is a stone I then run South 27 30 " to the S V Cor of the above named claim No/ 38 I identify this corner from the old B T s and the testimony of D Dyer I set a four inch stake for this cor and run East 14 45 " and fall 3 ft South of a corner I identify this corner as being a County Surveyor s corner from the old B T s The corner was set for the 1 sec cor between secs 21 and 22 above tp and range I then continue my line on South and at 22 74 " I fall 0 17 chs E of a large madrone stake marked 1/16 C S This stake was witnessed by two madrones trees marked 1/16 S C S B T I am informed that said corner was set by Isaac Hamilton I continue my line on south and at 48.60 " set stake and note that I fall 0 16 chs East of a large madrone stake set presumably by Isaac Hamilton I note that this stake is marked C S 21 22 27 & 28 and that the B T s are near and plainly marked At this point I make a very diligent search for the old B T s for the corner common to sections 21 22 27 & 28 but could find no evidence that such trees had ever grown in that vicinity I am also reliably informed that no other surveyor had ever found evidence of the oak witness trees and that said Hamilton had set his corner in from a line run from the north as my line had been I then discontinue survey at this time to await instructions from the Sur Gen Office and obtain more field notes

On July the 11th I resume the survey and set temp cor No 1 at a point midway between the Gov cor common th secs 25 26 35 and 36 and the N W Gov cor of sec 24 This N.W cor of sec 24 is readily estab from the old B T s and Gov field notes The position of this temp cor # 1 was obtained by calculation from the known position of Germond s S W Cor to sec 24 and the line that I had run from the south and above described Also this Temp Cor # 1 was set in by proportional measurements and on a direct line between the N W Corners of secs 24 and 36 according to Gov instructions I then return to Germond s S W Cor as recorded and still plainly in position and from his records of the line run from the known and estab Gov cor common to secs 25 26 35 and 36 to the N.W cor of sec 24

S 87 25