

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No.	Made on	Survey No.	Made on
In Town.	Range	In Town.	Range
Made for	Sec.	Made for	Sec.
Purpose of		Purpose of	
7.29 chs.	Cody Sur. Cont.		
37.13 "			
74.26 "			
71.52 "			
71.52 "			
20.00 "			
19.00 "			
19.73 "			
12.00 "			
2.00 "			
2.00 "			
12.42 "			

set
 and temp. cor. # A. This temp. cor. # A. was set in by proportional measurements and according to instructions for the S.W. cor of sec. 24. Now it is to be noted, that from my work and the work of Sur. Germond I have two positions of the S.W. Cor. of sec. 24., viz., temp. cor. # 1 and temp. cor. # A. I then according to instructions run a line west from temp. cor. # 1 and a line south from temp. cor. # A. and at the intersections of these two lines I estab. cor. # 1. for the S.W. cor. of sec. 24 See notes of estab. elsewhere.

I then run N.09°-23' E. on a true line and at

I set in cor. # 2 for the 1/4 cor. between secs. 23 and 24. I continue this line on northerly on the same bearing and at

I fall on the N.W. Cor. of sec. 24 as previously identified. I reestab. this cor. as noted elsewhere.

I then return to the cor. or cor # 2 between secs 23 and 24 and run a random line N.73°-34' E. across the said sec, 24 and at

I fell 0.26 chs. on the Gov. 1/4 cor. on the East side of sec. 24. I identify this cor. from old B.T.s. and Gov. field notes. I reestab. said cor. as noted elsewhere, and also number the same in my notes as cor. # 3. I then return on the true bearing of S. 73°- 21' W. through the center of sec. 24 and at

fall on cor. # 2. I discontinue survey here because of lack of help; the harvest season be in full blast.

On July the 30th. I resume the survey, by beginning at Cor. # 2. and run a line N.73°-21'E. through the center of the sec. At

I set in cor. NO. 4 as recorded, for the ^{N.W.} cor. of the N.E. 1/4 of the S.W. 1/4 of sec. 24. I then turn and run S. 10°-32' W. on a true line and at

I set in cor. # 5 as recorded, for the ^{S.W.} cor. of the N.E. 1/4 of the S.W. 1/4 of sec. 24. I then turn and run a line N.74°-47' E. on the south side of the N.E. 1/4 and at

I set in cor. # 6 for the S.E. cor. of the N.E. 1/4 of the S.W. 1/4 of sec. 24.

On July 31st. I resume the work at the Cor. # 6 and run a line N. 84°-55'E. to a point; then turn S.89°-47' E. and at

I hit the S.W. Cor. of the D. J. Craig Cl. # 37. I identify this cor. from the old Gov. Field notes and B.T. I then run a line East from this cor. and at

I set on the S. bdy. of the Cl. # 37. cor. # 7 for the N.W. Cor. of lot # 3 of sec. 24. From this cor. # 7 I run a line S. 06°-05' W. along the W. side of lot 3 to a point on the south side of the County Road and set in cor. # 13

I then return to the center of sec. 24 and set in cor. # 8 for this cen. cor. and from cor. # 8 I start and run a line N.11°-35' E.

to cor. # 9, which was set for the N.E. Cor. of the E 1/2 of the S.E. 1/4 of the N.W. 1/4 of sec. 24.

Again I return to the center of sec. 24 and retrace back along the center line of said section on a bearing of S.73°-21' W. and at