COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No. *Made on* Nov. 7 and 8th 1918	*Survey No.* *Made on* May 22 1918
In Town. 30 S. *Range* 4 West *Sec.* 32	*In Town.* 20 S *Range* 10 W. *Sec.* 31
Made for F.T.Reynolds	*Made for* School Dist. No. 41
Purpose of boundaries of a mining claim "Theredore"	*Purpose of* survey was to get boundary lines of school property
F. B. 14 = 45 R	R F. B. 14 = 45.

I began the sur. at a point numbered 4 which I assumed to be the center of the claim. This point # 4 is a 12" sq. fir stump. From point # 4 I run N.19°-09' E.

ft.					
750.00	to point # 2 wh. is a 8" X 50" fir post.	From point # 2 I run	N. 70°-51' W.	a dist. of
300.00	to " # 3 " " " 6" x 50" " "	From " # 3 I "	S. 19°-09' W	" " "
1500.00	to " # 6 " " " 6" X 50" yew "	From " # 6 I "	S. 70°-51' E.	" " "
300.00	to " # 5 " " " 6" X 60" Mad. "	From " # 5 I "	S.70° -51' E.	" " "
300.00	to " # 7 " " " 6" X 50" fir "	From " # 7 I "	N.19°-09' E.	" " "
1500.00	to " # 1 " " " 6" X 50" fir "	From " # 1 I "	S. 19°-09' W.	" " "
300.00	to " # 2 and the second point set.	These lines from point # 2 to point # 1 form		

the sides of a rectangle 600 ft. by 1500 ft. in dimensions. I made my tie to point # 1 by running a tie line N. 01°-31' E.

7.94 chains to the corner common to secs. 28,29,32 and 33 above tp. and rg.

A new Gurley transit used on survey. Work was well executed. All bearings are true sun bearings. Chainmen were J. Alward W.F. Hutchinson

F. C. Frear
Dep. Co. Surveyor

Survey No..... Vault 1 Env. 2 = CS 1/2

I began the survey at corner No. 1 which is a 12" X 12" X 12" sandstone marked with cross in center. From Cor. No 1, which is the S.W.Cor. of the school property I run a line North (mag. var. 21°-15' E.) and at

220.38'
3.43 chs. set a 12" X 12" X 12" sandstone marked with cross. I call this corner Cor. No.2 and turn rt. 117°-26' onto a line which bears S.62°-34' E. and at

247.50'
3.75 " set in corner NO. 3 which is a 3" fir stake. Thence from Cor. No. 3 I run S.04°-21'W.

58.08
0.88 " to Cor. No.4 which is a 3" vine maple stake. From Cor. No. 4 I run S.75°-52'W.

222.09
3.365 " to the begin. corner or Cor. No. 1. I then use a tie line S. 19°-14' E

3344.88
50.68 " to the S,E.Cor. of sec. 31 above tp. and rg. as made by Sur. Ford. I also, witnessed corner No. 1 with a 3" curly maple which bears S. 62°-00' W. 37½ lks.

W.A. McHargue & W.R.Daily Chainmen,

F. C. Frear
Dep. Co Surveyor