

64

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No.	Made on	Survey No.	Made on
In Town. 29 S.	Range 6 W.	In Town.	Range
	Sec. 14		Sec.
Made for Ronk, Smith & Sargisson.		Made for	
Purpose of		Purpose of	

I then go to the S.W.cor of D.L.C.No 42 which I re-establish as noted elsewhere and sight East to the S.E.Cor of D.L.C. 42 which I also re-est from old B.T. and run a line of stakes across, this line of stakes is about $\frac{1}{2}$ ch south of the present fence. I then return to the $\frac{1}{4}$ cor between Secs I3 & I4 and run N.04°20'E. on the Sec. line and at

6.38 ch I set cor. #4 a 1"X30"I.pipe for the S.E.cor.of Ronks & N.E.cor of Smiths Land. I then return to the $\frac{1}{4}$ Sec cor between Secs I3 & I4 and run N.88° 29'W. thru the center of the Sec. and at

20.85 ch I establish the I-I6 cor or cor #5 by setting a 2"X36"G.I.Pipe from which a 30"W.Oak brs. N.38 $\frac{1}{2}$ °W. 1.23 ch scribed C.S.I-I6 S.B.T. I then continue N.88° 29'W. and at

41.70 ch I set cor #6 which is the center of the Sec. by driving a 1"X30" G.I.Pipe from which a 8"W.Oak brs. N.88°W. 10 lks. scribed C.S.I-I6 S.B.T.
a 6" " " S.81 $\frac{1}{2}$ °E. 15 " " " "

I then continue N.88° 29'W. and at

81.30 ch I fall on the $\frac{1}{4}$ Sec cor between Secs I4 & I5. I then go to cor #1 and run N.02° 22'E. and at

19.28 ch I establish the I-I6 S. cor. or cor #7 by driving a 1 $\frac{1}{2}$ "X30"I.bar from which a 36"B.Oak brs N.39 $\frac{1}{2}$ °E. 3.I6 ch scribed C.S.I-I6 S.B.T. I then continue N.02° 22'E.and at

38.56 ch I fall on cor #5. I then run N.02°30'E. and at

6.38 ch I establish the N.W.cor of Smith's land or cor #8 which is a 2"X36"I.Pipe. I then return to cor #7 and run along O.W.Ronks south line as follows
N.88° 31'W. 20.10 ch. Thence
N.87° 27'W. 40.09 ch. to cor #2

I then go to cor #6 or the center of Sec. I4 and run N.00° 25'E. and at

19.40 ch I establish the I-I6 S. cor or cor #9 which is a 4"X36" Oak stake from which a 24" W.Oak brs. N.50°E. 4 lks. scribed C.S.I-I6 S.B.T. I then run S.88° 05'E.and at

21.50 ch I establish the I-I6 S.cor or cor #10 which is a 4"X36" oak stake from which an 8" fir brs. N.65°W. 17 lks. scribed C.S.I-I6 S.B.T.
a 10" " " N.84 $\frac{1}{2}$ °E. 11 " " " "

I then run N.02°30'E. and intersect the south line of D.L.C.#42 at 0.32 ch. east of the S.W.cor and set a 4"X36" stake which I call cor #11.

Chaining fair.
W.& L.E.Gurley light Mt. Transit used
Bearings taken from sun by direct observation.

Chainmen { Hyman Huntley
Lou Sardonson

J. C. Fear
Deputy County Surveyor