

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No.	Made on		Survey No.	Made on	
In Town.	Range	Sec.	In Town.	Range	Sec.
Made for			Made for		
Purpose of			Purpose of		

MARKS ° WOLLENBERG SURVEY CONTINUED.

From hub near corner No. 3 at the center lines of the county roads  
 thence N89°40'W 1060.8 ft to corner (A) from which the corner between  
 sections 1 & 28 bears North 1310.2 ft. and West 549.2 ft. also from  
 which an iron pipe 1"x30" bears N 0°39'W 20 ft. thence N0°39'W 2628.7  
 ft. to corner (B) set and oak post and an iron pipe 1"x30" from  
 which A. Oak 15" dia S52°30'W 22 ft. , thence S89°29'W 524.5 to corner  
 (C) which is an iron pipe 1"x30" also an oak post , being the legal 1/16  
 corner . Thence N0°17'W 1318.8 ft to corner No. (12) previously described  
 thence S89°24'W 516.9 ft. to corner (D) , set an oak post also an iron  
 pipe 1"x30" from which a B Oak 28" in dia brs. S28°15'W 23 ft. Thence  
 N0°39'W 338.2 ft to corner (E) which is the N.W. corner of D.L.C. No. 43  
 which I located from the original bearing trees, set 4"x4"x40" Oak post  
 also an iron pipe 1"x30" (see record book of renewed Government Cor's  
 in County Surveyors office for record of new trees) Thence N81°52'E 822.3  
 ft. to corner (F) set an oak post also an iron pipe 1"x30" from which  
 A.B. Oak 24 " in dia. brs. S80°E 40.5 ft. , Thence S0°39'E 4295.4 ft.  
 to corner (G) on the center line of the county road, from which an iron  
 pipe 1"x30" bears N0°39'W 20 ft.

