

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No.	Made on	Nov 4-5-7-8-1921	Survey No.	Made on	
In Town.	29 S	Range	5 W	Sec.	11
Made for	Mr. Geo. Wixon and Mrs. Alice Colchasure			Made for	
Purpose of	Legal Survey. To establish lines and corners for W 1/2 of NE 1/4 of Sec. 11			Purpose of	

I began at temporary cor between Sec 2 and 11 which I set from a 2 ft B.O. assumed to be a B.T. . The B.O. bears N.65°E and a hole of a stump S70°E. The Oak had been cut open about 15 years ago and the heart had rotted out. Thence I run a random needle line, Var. 21°15' E, South and intersect the section line between 11 and 14 146.0 ft East of the quarter corner between said sections and 5155.0 ft from temp. quarter corner between 2 and 11. Chaining poor, hills long and steep weather dark and foggy. I find one witness tree, a 24" B.O. the other tree had gone. I establish the quarter corner by driving a 4" squared white oak stake N30°E 116.0 ft from B.T. and blazed 10" Maple , N45°E 84.3 ft for new witness tree. Corner sets on steep side hill.

I found three witness trees for sec. corner 1-2-11-12. The fourth tree , a B.O. has gone. I set a 4" squared white Oak post for Sec. corner from the three B.T. and set a new B.T. an 18" Fir, N 90°W 28 links. From this corner as established I run a needle line So, Var 22°52' E (No sun) and find quarter corner for sec 11 & 12 I set a 3" squared W.O. post for corner from the original witness trees as per field notes, set up at corner as established and intersect my random line 2.126 chains East of said corner and distant 39.43 chains So. of the Sec. Cor. point of beginning. Chaining was good, using triangulation and slope measurements. I drop back to the one-sixteenth corner set at 20.0 chains from sec. cor. on random line, and move that back North 29 links and West 106.3 links.

I set up at the sixteenth corner thus found, correct Variation by a solar observation, finding Var. to be 21°02'E and run needle line N 90° W. At 20 chains set a 3" W.O. post for approx. Sixteenth corner. A 36" Laurel Bears N 30° W 33 links and a 8" B.O. bears S 84°W 18 links. Thence I run 19.96 chains more , same course and set temp. stake for sixteenth corner . Set up on this stake, correct Var. from solar observation. Var. is 21°25'E and run needle line N to find quarter corner bet. 2 and 11. Can find only corner that we assumed was correct at beginning of survey. We found evidence of scribe mark in the bark and there was also considerable evidence of an old blaze on the B.O. that had been cut open 15 years ago. This tree checked with some old blazes that we assumed were line blazes between sec. 2 and 11 so I reestablished the quarter cor. from this tree, set a 4" squared W.O. post and marked new B.T. 12" Fir bears N 76° W 13 ft. 10" Fir S.18° E 22 ft. I set on this post and intersected line I had just run from the sixteenth corner south of this quarter corner at 1328.1 feet from said sixteenth corner and the random line intersected the section line between 2 and 11 123.5 feet West of quarter cor. I then returned S 1328 ft to the sixteenth cor as temporarily set and moved that cor E 90.7 ft as found by taking one fourth of the distance, 146.0 ft, that I intersected E. of the quarter cor. between sec 11 and 14 on the first line I ran, thus making the distance of this cor. 1328.1 ft So of quarter cor between 2 and 11 and approx. 2546.7 ft W of sec. line between 11 and 12. Set a 4" squared W.O. post for cor. 24" Fir bears N 64° W 152.4 links and a 24" Fir S 42° E 63 links.

This location of the corner was approximately correct and satisfied Mr. Geo. Wixon who did not wish to bear expense of an accurate subdivision of the N.E. 1/4 of sec 11. No representative of Mrs. Alice Colchasure was present.
G.C. Stewart Deputy. C. Crocker and Geo. Wixon, chain. A.W. Yokum Axeman.

Legal Notices sent to Mrs. Alice Colchasure and Mr. Geo Wixon at Myrtle Creek, Oct. 27

