

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

<b>Survey No</b>	<b>Made on</b> March 1922	<b>Survey No</b>	<b>Made on</b>
<b>In Town</b> 28 S	<b>Range</b> 7 West	<b>In Town</b>	<b>Range</b>
	<b>Sec.</b> 3-4-		<b>Sec.</b>
<b>Made for</b> B F Caldwell, Roseburg		<b>Made for</b>	
<b>Purpose of</b> Legal Survey, to establish lines and corners for fences		<b>Purpose of</b>	
G G Stewart, Deputy			

*FN Loose Leaf*

Legal Notices having been mailed to B F Caldwell, Wm Voorhies, T F & Nettie Heard, Fred and Anna Neureiter, Frances E Burchard, Jay H Bronk and Alexander Erickson of Lookingglass, on Feb. 20 1922 I started survey on March 3rd at the quarter corner between sec 9 and 10 where I found one O B.T. and one O.B.T. that had fallen I set an I Pipe for corner and marked a new B T a 10" Fir N 51°E 22.0 feet, the O B.T. was a 18" B O N 80° W 14.5 ft Caldwell, Strickland, & Dysert witness From this corner as set I run a tacked transit line North to the location of section corner common to 3-4-9-10 but could find no evidence of this corner, all B Ts being gone I continued line North to the quarter corner between 3 and 4 and found the stumps of both O B Ts I set Iron Bar for corner and arked a 12" Fir S66° W 50.0 feet, a 24" B O bears N 53°W 163.0 feet Corner set in presence of B F Caldwell, A Dysert, A O. Strickland and A. Erickson From traverse as run I compute length between quarter corners as N 89° 48' W 5280 0 feet Var 21°04

Next I go to the quarter corner between sec 4 and 9 Found the O B T a B Oak well rotted and remarked I set a gun barrel for corner and marked new witness trees A 8" Laurel bears N 54° E 29 0 feet and a 12" Pine bears S 4° W 56 0 feet Corner set in presence of Erickson, Dysert and Strickland From this corner as set I run a transit line East to the quarter corner between 3 and 10 I find the stump of the O B T and this stump has the letters "B T" scribed on it I set a squared cedar post for the corner and marked a 8" W Oak N 83½° W 48 5 feet 18" B O. bears South 35 4 feet Corner set in presence of Strickland, Dysert and Erickson From the traverse as run I compute the length of line between quarter corners as N 89°54' E 4865 4 feet I place two points on line on the lines run North and South, and East and West and at the intersection I locate the Section corner common to sections 3-4-9-10 and drive an Iron pipe for the corner, about 8 feet from edge of Co road I mark a 16" B O. N63°E 71 9 ft and a 10" B O. N 11°W 24 7 ft No other trees available Set in presence of Strickland Dysert and Erickson

From the traverse as run I compute the length of line between section corner as established to the quarter corner between 4 and 9 as 2622 1 ft Midway between these two corners I set the sixteenth corner, or the SW corner of B F.Caldwells property, set a 1" Iron Bar for corner and marked a 12" B. O. S 86° E 30 8 feet

I compute the length of line between section corner as established and the quarter corner between 3 and 4 as 2687 6 feet and midway between these corners I set the sixteenth corner Drove and Iron pipe and marked a 24" White Oak N34° W 20 5 feet

Weather, partly rain and dark Chaining done with 300 ft steel tape slope measurements, angles doubled and part of chaining rerun. Work carefully done

C Crocker and W X. Crearer chainmen

