

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

<p>Survey No. Made on March 18 1922</p> <p>In Town. 26S Range 3 W Sec. 10 -15</p> <p>Made for Fence Line for C .J Green</p> <p>Purpose of</p> <p style="text-align: center;">G G. Stewart, Deputy</p>	<p>Survey No. Made on</p> <p>In Town Range Sec</p> <p>Made for</p> <p>Purpose of</p>
EN "11"	CS 1/51

I start at the SW corner of section 10 where I find the stump of O B T and one O.B T , a Sugar pine standing I reset the corner, putting in a 6" x 6" x 16" stone with a cut on top for the corner I remark a 42" Fir South 616--ft 61 6 ft, 30 " White Fir N 47°W 56 0 feet Sugar pine 24" S 80° E 22 links, Original B.T No other tree suitable Max Shellabarger and M.L Kimmel, witness. From this corner as established I run a tacked transit line to the quarter corner location between sections 10 and 15 but all trees are cut down and I cannot find corner I continue transit line to the section corner common to 10-11-14-15 and find one Original B T standing, others down and rotten I reset from this tree and put in a 1" Iron pipe with a yew marker and blaze a 36" Fir N 46° W 16.5 ft, 30" Fir N 30° E 21 7 ft, 24" Fir S 58° E 42 7 ft and a 10" Yew S 41° W 19,0 ft Max Shellabarger and M. L Kimmel witness From the traverse as run I compute the length of the section line on the south side of section 10 to be N 89°25' E 5237 7 feet

I set a two inch iron pipe for the quarter corner between 10 and 15 and mark a 12" Cedar S 15° E 65 0 ft and a 18" Dead Maple N 31° E 22 0 ft. The corner as set was half way between section corners as set, I also set a post for the sixteenth corner East of the quarter corner.

Line carefully run, slope measurements, triangulation Weather fair Variation 21°15' W S Crearer Chainman

