

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

Survey No. Made on May 1922
 In Town. 32 S Range 4 W Sec. 6-7
 Made for H. J. Wilson, B. Neff, Robert Payne, Glen B. Booth et al
 Purpose of Establishing lines and corners.

Survey No. Made on May 22 1922
 In Town. 29 Range 9 W Sec. 36
 Made for E. J. Kennedy
 Purpose of Boundary

MAP FILE M3-7-32
 G. G. Stewart, Deputy F.N. LL

G. G. Stewart Deputy F.N. LL

The accompanying map is a part of this record. I went to section corner #1 which I reset from the stumps of the O.B.Ts. all trees being down. I set an iron bar for the corner and marked a 24" Fir N16° E 183.2 feet; 30" Fir N 71° E 216.0 ft No other trees available. From this corner as set I ran a traverse line to the 1/4 section corner # 3 where I found the stump of the O.B.T. and I set an iron bar for this corner and marked a 12" Fir N 89° W 218.0 ft; 10" Fir N 56° E 143.0 ft. I compute the distance from #1 to #3 to be N 0° 01' W 2640.9 feet. I set a line of stakes from my traverse line, on the true line and set the sixteenth corner # 14 midway between. Drove an iron bar and marked a 12" Laurel S 39° E 29.5 ft. I then ran from #1 corner to the quarter corner #2 where I found one O.B.T. standing and one badly burned. I set a stake marker by side of brick for corner and marked a 18" Pine N 43° E 45.6 ft; a 18" Pine S 27° W 20.0 feet. From traverse I compute the length of line from #1 to #2 to be N 87° 05' E 2748.3 feet. I set a line of stakes on the true line for fencing.

From #3 I ran a traverse thru the center of section 7 to the quarter corner #5 . The O.B.T. is standing but I did not set the corner. I compute the length of this line to be N 87° 40' E 5344.0 feet. From #2 corner I run a traverse line to the quarter corner #10, where there was a stake scribed 1/4 S and witness trees, made by a previous County Surveyor. There was no record of this corner being so set and its location did not suit any interested parties, who showed me the stub of a yew stake burned off at ground and with a big stone marker which they claimed was the corner, from statements made to them all by a Mr. L. W. Barber. Barber owned land cornering at this corner and he bot it in 1872, about a year after it was first surveyed and he was present at time of survey. After the stake had burned off he claims he set the rock. There was no signs of witness trees. Robert Payne, Burnham Neff, H. J. Wilson K. H. Cooper and G. A. Pickett, signed a statement to effect that this was correct location for corner, and agreeable to them. I drove a 1" Pipe at this point and marked a 12" Cedar S 51 1/2° W 9.0 ft; a 10" Cedar N 7 1/2° W 178.7 ft. From traverse as run I compute the length of this line from #2 to # 10 to be N 1° 22' W 5292.9 feet. I set straddle hubs on the true lines as run thru center of section, and located corner #4 where I set an iron pipe and marked a 36" Fir S 7° E 64.0 ft; a 6" Fir S 40° W 62.0 ft Midway between # 4 and # 10 I set the sixteenth corner # 6 and drove an iron pipe; no trees available.

From # 3 corner I ran a traverse line to the section corner # 9 where I set an iron pipe for corner from two O.B.Ts; the others are down. Marked a 18" B.O. S 44° W 121.0 feet; a 20" B.O. N 5° W 95.2 ft; a 10" B.O. S 30° E 47.4 ft(O.B.T.) and a 30" Pine N 54 1/2° E 26.8 ft(O.B.T.). I compute the bearing of this line to be N 0° 36' E 2640.4 ft and I set the sixteenth corner midway between, # 8 corner. Set an Iron Pipe for corner and marked a 20" Fir N 80° W 6.2 ft. From # 8 I ran a traverse to #6 and I compute this line to be N 87° 26' W 2660.9 feet. I set # 7 midway between and drive an iron pipe and mark a 12" Ash S 55° W 37.5 feet.

From corner # 10 I run a needle line N 0° 16' E 1320.0 feet and set # 11. Drive an iron pipe and mark a 12" Laurel S 89° W 7.5 ft; a 10" Laurel N 43° E 11.8 ft. From # 11 I run a needle line N 89° 28' E 1320.0 ft to # 13 corner, where I set a stake and mark a 48" Fir N 30° E 204.5 ft.

Chaining carefully done but not checked. Used a 300 ft tape, vertical angles, coordinate system of figuring courses. Solar bearings. W. S. Crearer, Chainman . Present as helpers, H. J. Wilson, W. H. Damewood, Sr. B. Neff, K. Cooper.

E. J. Kennedy;

I began at the section corner common to sections 25-30-31 and 36, as set and recorded by Cole. I ran a tacked transit line to the quarter corner between sections 31 & 36 where I found the original B.Ts. I set an iron pipe for the corner and remarked the witness trees. From the traverse as run I compute the length of this line to be North 2775.4 feet, variation 20° 52' E. Magnetic. I set the sixteenth corner midway between and set an iron pipe from which a 12" Cedar bears N 49° E 47.7 feet. From this sixteenth corner as set I run a transit line due West 311.0 feet to the Southeast corner of Kennedy's land. I set an iron pipe and mark a 6" Fir N 65° E 16.0 feet. I continue West and at 340.2 feet I set an iron pipe on the East bank of the Middle Fork of the Coquille river. The corner of Kennedy's land is in the center of this river. I return to the initial point, the Southeast corner, of Kennedy's land and run N 9° 46' W 508.0 feet to an iron pipe from which a face of rock, 6.0 feet high bears S 82° E 21.0 feet. From this point I run due West 138.8 feet to the bank of said river and set an iron pipe for witness corner; the true corner comes in the middle of stream.

W. S. Crearer, chainman. E. J. Kennedy backflag. Weather clear.

FD. 1915
 ORG. ST. Hwy
 Dept. N-B

