

127

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

<p>Survey No Made on Nov 1 1922 In Town 28 S Range 47 Sec 29 Made for Frank Beck et al Purpose of Subdivision section and fence lines</p>	<p>Survey No Made on In Town Range Sec Made for Purpose of</p>
---	---

G. G. Stewart Deputy

TRACING IN C.S. File No. 3/27

E.N. 111

No Legal Notices were given, but parties to survey signed following statement "We agree to accept survey made by Deputy County Surveyor G. G. Stewart, Nov 1 1922 as Legal Survey and waive the customary Legal Notice" Signed by O. E. Leighton, J. L. Paris, Frank Beck, G. A. Copeland, T. Lowden, J. Thomason, by Jess Thomason

I went to section corner common to sections 28-29-32-33 where I find witness trees in good shape. I ran a transit line, Var 21° 15' E to the quarter corner between 28 and 29. Could find no trace of witness trees so I continued to section corner common to sections 20-21-28-29 where I found one O.P.T. and stump of another. I set good squared stake and marked new trees 36" Fir N 5° E 46.3 ft, 10" Yew S 47½° E 71.0 ft, 36" Fir S 24° W 12.0 ft and 30" Fir W 45° W 72.1 ft. I compute length of line to be N 1° 01' E 5484.8 ft. I set the quarter corner midway between and drove iron pipe and marked 18" Cedar N 43½° W 59.5 ft, 24" Cedar S 63° W 144.7 ft. I set the sixteenth corner North of ¼ corner, drove a stake and marked 24" Laurel N 70° W 22.4 ft. The sixteenth corner South of ¼ corner, drove a stake and marked 30" Fir N 49° E 49.0 ft. From this corner I ran a needle line East at bearing of S 89° 00' E for fencing purposes. I returned to starting corner and ran East to ¼ corner between 29 and 32 where I found O.P.T. and stump of other. Set Cedar post and marked 48" Fir N 23½° W 30.2 ft, 18" Fir S 9° E 40.7 ft. I compute length of line to be N 88° 36' W 2539.1 ft. I continued line to section corner common to sections 29-30-31-32 where I found 2 O.P.T. and 2 stumps. I set corner according to distances from trees and stumps. Drove pipe and marked 8" Fir S 15½° W 6.0 ft, 18" Cedar N 30½° W 46.8 ft, 18" Cedar S 87½° E 49.5 ft and 18" Fir S 83° E 52.8 ft. I compute length of this line to be N 86° 54' W 2613.4 ft.

From ¼ corner between 28-29 I ran to the ¼ corner between 29-30. I found one B.T. an Oak, but it was opposite quadrant from field notes, I also found stump of other B.T. which checked for angle, but in opposite quadrant. I chained to top of hill as per field notes, from this corner and it checked within 5 ft. I take this to be original tree and set corner from there. Set post and marked 30" Y Pine S 34° E 30.2 ft, 14" Cedar S 15½° W 43.0 ft. I ran to the ¼ corner between 20-29 where I found two O.P.Ts, one badly rotted and other burned. I set iron pin for corner and marked 24" Fir S 10° W 42.2 ft, 20" Cedar N 12½° W 31.6 ft. From system of coordinates used I compute position of center of section, setting it midway between ¼ corners, on North and South sides, and East and West sides. Drove iron pipe for corner and marked 18" Fir N 88½° W 90.4 ft and 24" Fir S 57½° E 52.6 ft. I set the sixteenth corner East of this corner, set a post and mark a 24" Laurel S 6° W 9.0 ft.

C. Crocker, chairman, G. A. Copeland rear flag man, Frank Beck, Leighton Thomason, present most of time. Weather cloudy, magnetic bearings used. Slope measurements and vertical angles used and angles doubled. Work carefully done.