

1408  
**COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON**

BISHOP & CO. PORTLAND, ORE 87545

<p><b>Survey No.</b>                      <b>Made on</b> August 30 1922</p> <p><b>In Town.</b> 30S      <b>Range</b> 5 W      <b>Sec.</b> 17-18</p> <p><b>Made for</b> Russell J. Frauley</p> <p><b>Purpose of</b> To establish line between sections 17 and 18</p> <p>Ben. B. Irving Surveyor          E. Richardson Chain          Edges Flag          Frauley</p>	<p><b>Survey No.</b>                      <b>Made on</b></p> <p><b>In Town.</b> 28 S      <b>Range</b> 6      <b>Sec.</b> 17, 18 19 and 20</p> <p><b>Made for</b> Wm. &amp; Chas. Buxton</p> <p><b>Purpose of</b> Establish line between sections 17, 18, 19 and 20</p> <p>Ben. B. Irving Surveyor</p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

FN. LL.      FN. LL.      C.S. 5/14

I began the survey at the corner common to sections 17, 18, 19, and 20 which is an iron pipe set by Gordon Stewart a Deputy Surveyor in 1922. I then ran a traverse in a Northerly direction to the corner common to sections 7, 8, 17, and 18. I then figured the true line between sections 17 and 18 to be N 0° 18' E 5595.5 ft.

March 16 1923

Subsequent to the recording of this survey Gordon Stewart moved the corner common to sections 17, 18, 19, and 20 to the North and West an unknown amount.

Ben. B. Irving

Beginning at the  $\frac{1}{4}$  section corner between sections 17 and 18, I ran a traverse south to the corner between sections 19, 20, 30 and 29 which I reset from the original bearing trees, two of which were still standing. I found this line to be S 0° 40' W 8050.1 ft. In as much as the interested parties merely wished this line and the proportionate section corner on this line I set a pipe in the field from which a rock outcrop bears N 44° 37' W 191.5 ft., another outcrop bears S 84° 30' E 790 ft., and the north end of Wm. Buxton's barn bears S 66° 40' E