146

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO PORTLAND, ORE 87545

Survey No. *Made on*	*Survey No* *Made on*
In Town. *Range* *Sec.*	*In Town* *Range* *Sec.*
Made for Coets • Newland Survey Cont'd	*Made for*
Purpose of	*Purpose of*

M 1-2

HUB NO.	BEARING	DIST.
110		
	N7°47E	180.4
111		
	N72°36'E	288.4
112		
	North	166.2
113		
	North	164.8
114		

Corner No 2 on Plat No.114 52°26'W 75.6 ft to the , Corner set by Ford I determined the position of this corner by the faces of the Original Bearing trees which I found and chopped baring the scribe marks which were plain, but the faces of the trees did not correspond with the directions given, the position which I chose for the corner also checked with the distance given by Hathorne in his resurvey, from the Section corner North , as shown by a continuation of this traverse North to Hathorne s Sec Corner.

114		
	N1°57'E	37122
115		
	N5°17'E	212.2
116		
	N6°37'E	210.7
117		
	N6°35'E	229.8
118		

Corner No. 1 on Plat No 118 is Hathornes Section Corner which I renewed from the Original Bearing Trees both are still Standing See book of Renewed Gov't Corners

I then returned to Hub No 103 and searched for Evidence of the Original BTs and foound a large stump that had been cut by Mr Newland for wood and Mr Coets says that he and heard Mr Newland say that he had cut one of the BT's for wood in that vicinity and there being no other stumps that could correspond I accepted the identity of the tree as being the Orig. Pt. and ran N85°W 1917 lks and set and Iron pipe " 2"x30" for the corner and marked new trees as follows

• .Oak 14' in dia N53½°W188.0 ft.

A.W. Oak 30' N84°E 67.5 ft. A. Oak 20" S09°40'W 539.0 ft.

From Hub No 103 this corner which is Corner 6 on Plat and is the South West Corner of Sec 30 brs. N9°W 78.0ft.

I next went to the ¼ Corner on the North Bd'y of Section 31 which is Corner 32 on the Plat and ran S88°26'W 1493.4 and set and Iron buggy Axle for the 1/16 Cor. the distance proportioned as follows, 20.00 Chs. divided by 43.10 Chs multiplied times the remeasured distance of 3218.5 being 1493.4

Traverse to locate the ¼ Cor on the South bnd'y of Section 31 set at Hub No 315 near the SW cor. of Lot 5 Sec 31 thence I ran

315		
	S0°55'E	251.9
316B		
	S11°53'E	594.1
317B		
	S46°18'W	143.8
¼ Corner		

I determined the location of this corner by using the ties given to this corner in the field notes of the McCulloch DLC #37 although the dist. of the ¼ Cor West of the DLC line was 13.33 Chs I changed it to 3.33 Chs which brought this corner on a continuation of the line of fence North of the corner said fence being in place for a great many years and placed on the survey of the John Coats homestead which was intended as a partial subdivision of the Section according to the testimony of W.H Coats who was born and lived there 60 years and who seemed to understand the lines thouroughly He also testified that Tom Mcculloch had said he had dug out the witness trees for this corner while preparing a garden and my renewed corner came in the South end of the old Garden, also the tie given to the creek checked closely

The ¼ Cor. as set by Stewart bears North and West several hundred feet