

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BEVING & CO. PORTLAND, ORE. 87345

Survey No.	Made on	Survey No.	Made on		
In Town.	Range	Sec.	In Town.	Range	Sec.
Made for			Made for		
Purpose of			Purpose of		

I then returned to Hub No. 23A and ran North 192 ft. and West 72 ft and set an approximate 1/16 corner for the North Corner of Felix Hudson's land, I set a rock 10"x10" x12" from which a Fir 18" in dia S28°E 20.4 ft.

I then went to Hub No 5 B and set the approximate 1/16 corner in the center of the SW 1/4 of Sec 28, I ran South 100 ft and East 124 ft and set a rock 10"x10" x12" for corner from which A Fir 50" in dia N10°30'E 24 ft.

I then when discontinued the survey and sent for Government field notes of the lines between Section 28 and 33 and on May 28 1923 continued the survey, I went to hub No 9 and continued westerly as follows, N87°00'E 7817 ft to Hub No. 10 thence S89°48'E 172.0 ft to Hub No 11 Thence N87°38'E 362.5 ft to Hub No. 12 Thence S22°30'E 88.8 ft to Hub No 13, Thence S80°E 248.0 ft to Hub No 14, Thence S30°30'E 80.8 ft to Hub No 15 Thence S36°00'E 75.0 ft to a spring called for in the Government field notes for the section line between Sections 33-34, From this, spring I ran North 148 ft and made diligent search for the bearing trees to the Section corner but could find none, From the tie to the spring I computed the length and bearing of the line between 28 and 33 as N89° 46 E 5467 ft.

I then returned to Hub No 5 and made diligent search for the quarter corner 184 ft North of Hub No 5 but could not find anything as this area had burned over and killed all small trees,

I then went to Hub No 9 and corrected the lines of the survey as follows From hub No 9 I ran South 58.3 ft and East 294.7 ft and set an approx 1/16 corner for the South East corner of Felix Hudson's land, an Iron bar 1/2"x2"x24" from which A Fir 36" dia brs S 25°30' 32.5 ft.

I then to Hub No 9 A and ran North 128 ft and East 122 ft and set stake for the approximate 1/16 corner in the center of the South East quarter of Section 28

I then went to hub No 15 A and ran North 138 ft and East 180 and set a stake for the approximate 1/16 corner on the 1/4 line North and South in the center of the south half of the section

I then went to Hub 19A and ran East 120 ft to West bndry of Hudsons land but did not attempt to set the approximate 1/16 corner North as the land was too mountaineous.

The lines were blazed between corners as shown on the plat .