COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

Survey No. *Made on*

In Town. *Range* *Sec.*

Made for

Purpose of
Voytilla-Parkinson Survey cont'd.

Survey No. *Made on* Feb. 10, 1927

In Town. 29 S. *Range* 7 W. *Sec.* 1.

Made for Voyilla-Parkinson-Smith

Purpose of Get the approx. Center of the Section 1/

I established the one quarter corner between Sections 1&12 as follows
An Iron pipe 1"x36" and a cedar post 4"x4"x30" from which
/ Maple 12" in dia brs S76°30' E 10.7 ft.
/ B Oak 8 in dia N43° E 27.0 ft

The one Sixteenth corner between Secs. 1-12 and west of the one quarter corner I set a fir post 3"x3"x36" from which
/ Laurel 15" dia brs. S82° E 21.0 ft.
/ Laurel 18 " S48°E 6. 5 ft.

The one quarter between Secs. 2-11
Set an Oak post and a rock 6"x6"x12" marked 1/4 S from which
/ Fir 18" in dia brs. N72° E 17.2 ft.
/ Fir 12" " S57°30' E 22.0 ft.

The One quarter corner between Sections one and two
I set a Fir post 4"x4"x30" from which
/ Fir 30" in dia brs. N30°E 3.0 ft.
/ Fir 18" in dia brs. S86° E 27.5 ft.

The Sixteenth corner between Sections 1-2 and South of the One quarter cor. I erected a rock mound 24" in dia and 15" high also a Maple post from which / Fir 24" in dia N48°30' E 29.0 ft.
/ Fir 30" in dia brs. S12°00' E 1 .ft.

The Section line between sections 1-12 was blazed through-out
The Section line between 2x11 was not blazed.
The Section line between 1-2 was blazed from the one sixteenth corner described above, to approximately one quarter mile North of the one quar. corner

---

The North, east, and west boundaries of the land shown as Charles Voytilla were run only approximately and were kept seperate from the survey above shown.

Solar Observation

Taken near the corner to Sections 1-2-11-12;; 3:30 PM Oct 17 1923

Dec of Sun at Greenwich noon	South 8°58'22"
Hourly change 35.17"x11 hours	10'06"
Dec. of Suns at time of observation	South 9°08'28"
Latitude of Base line	North 45°31'
Correction for 28 1/6 To mohipe	2°26'
Latitude of observation	North 43°05'
Suns measured altitude	19°31'
Refraction correction	09'

°51' Right
from the
ft 0°53'

l ,as established
corner and back-
he Approx.
Pine Bears 14° 0C' W.

ie attached

nd Smith.

Surveyor.

AN AGREEMENT

We the undersigned interested parties agree to accept line, run by H. L. Eppstein, County Surveyor, on this 17 day of February, 1927; using as a starting point a corner previously established by J. W. Cole, a former County Surveyor, on a legal survey made by him on October 15, 1923. Recorded in Vol. 3 Page 171 Co. Surveyor office

Dated this 17 day of February, 1927

Witnesses:

J. W. Woolford

H. L. Eppstein

Charles C. Voytilla

Robert J. Smith

Chas. Parkinson