

187

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

<p>Survey No. 1-26 Made on June 24, 1924 In Town. 22 Range 6 Sec. D.L.C. 37 Made for Snell Estate Purpose of Division of Estate</p> <p>Vault #2 Env. 26 = C.S. 2/26 FB 24D. B 16 FB 24 = 53</p>	<p>Survey No. Made on In Town. Range Sec. Made for Purpose of</p>
--	--

<p>Feet</p> <p>4293.7</p> <p>347.4</p> <p>East</p> <p>1327.8</p> <p>1547.5</p> <p>South</p> <p>2611.5</p> <p>241.9</p>	<p>I began the survey at the North west corner of D.L.C. No 37 which identified by the B.T. as the original corner, and ran South 60° East on a random line and at</p> <p>fell 130 ft. South of a stone on the north line of the D.L.C. 37 and the boundary line between lot 5 and 6 of Sec. 8 of the above twp and range.</p> <p>I then returned to a point on my random line 1320 feet East of the Northwest corner of the claim and set an iron pipe on the true ix North line of the D.L.C. and the Northeast corner of a tract for Ada Hicks.</p> <p>I occupied this corner and ran a line S 30° W parallel with the West boundary of the D.L.C. and intersected the South line of said claim 127 feet East of the corner set by rear on the South line of the claim and on the line between Sec. 7 and 8.</p> <p>I then returned to the stone monument between lots 6 and 5 in Sec. 8 and ran North</p> <p>as given in the Govt. Field Notes to the NW Cor of the 6 of Sec. 8 thence on a random line between Lot 6 and the Net of Set of Sec 8 and at</p> <p>set a stake as temp. point on random line</p> <p>set a stake as temp point on random line</p> <p>I then went to the $\frac{1}{4}$ corner between section 8 and 9 which I renewed from two old trees which showed blazes with traces of scribe marks. A iron bolt set by the surveyors that platted the Sunnydale Orchards answered to the distances and bearings given by the govt. field notes from the dead trees assumed to be the B.T. of the corner. I remarked the trees as recorded in the book of renewed corners. Thence I ran on a random line and at</p> <p>I fell 158 feet East of the section corner common to sections 7-8-16-17 which was an iron pin with original B.T. standing. I then returned to point equal distant between the above corners and set a stake for the Northeast corner of Lot 6 of Sec. 8. I then corrected the random lines on the North and East boundaries of Lot 6 by blazing trees and setting stakes on the true line. I found that the length of the North boundary of Lot 6 was 1335.6 feet.</p> <p>I then went to a point in the center of the county road and on the line between Sections 8 and 9 65.4 feet North of the Section corner common to Sections 7-8-17-16 and ran up the center of the old county road as follows, S 85° 09' W</p> <p>S 51° 56' W 323.8 ft., S 29° 38' W 228.4 ft., S 73° 11' W 238.0 ft. S 84° 26' W 233.4 ft., N 86° 04' W 443.2 ft., N 28° 07' W 308.0 ft.,</p>
--	---