

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

Survey No. 3-28	Made on Nov. 16, 1925	Survey No.	Made on
In Town. 28	Range 5	Sec. 15-16	
Made for A.B. Hatfield & L.C. Patterson		Made for	
Purpose of Sec. line W 60 Ac. of NW <sup>1</sup> of 15		Purpose of	
Survey by W.H. Wood			
Chain W.S. Crear			

F.N. "LL"

At the 1/4 corner to Secs. 15 and 16, I find the B.T.s in good shape and renew corner by setting a 6"x 6"x 2.5' oak stake scribed 1/4 S 15-16 C.S. thence

North  
40.06

On a random line  
To corner of Sections 9-10-15-16 which I renew as follows-

I find stump with scars but with scribe marks rotted out ~~mark~~  
N 56<sup>1</sup>/<sub>4</sub> W 5.20 and a oak S 40<sup>3</sup>/<sub>4</sub> E 4.00 and an Oak S 30<sup>1</sup>/<sub>4</sub> E 1.90

The distance given for the last bearing tree is given as 4.90 but appears to be in error and I set the corner from the first two bearing trees. I set a 4"x 4" x 2.5' oak stake scribed S 9-10-15-16 C.S. and marked

An Oak 12" in dia. N 69°30' W 51 lks. B.T. S 9 C.S.

East  
15.00  
40.19

On a random line (Corrections)  
Set a temp. point Moved south 36 lks.  
Fell 96 lks N or Cor

At 1/4 corner to 15-10 I find both B.T.s in good shape and set a 4 x 4 2.5 white oak stake marked 1/4 S 10-15 C.S.

For the Northeast corner of the 60 acre tract I set a stake on line between the cor. to sec. 9-10-15-16 and the 1/4 cor. to sec. 15-10 at a point 15.00 ch. East of Cor to 9-10-15-16.  
I set a stake East 15.00 Ch. from the 1/4 cor. to 15-16 at approximately the S.E. corner of the 60 acre tract.

