

217 COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

EUSHORE & CO. PORTLAND, ORE. 57545

Survey No. Made on Nov. 12, 1926 to
 In Town. 30 S Range 5 W Sept 1, 1927 Sec. 18
 Made for J.W. Fitzpatrick et al
 Purpose of to establish 1/4 corner between
 Sections 17/18, East line of Sec.
 18 and east and west 1/2 section
 line thru Section 18

Survey No. Made on
 In Town. Range Sec.
 Made for
 Purpose of

C.O. #3 F.N. "LL"

Legal Survey called for by J.W. Fitzpatrick. Notices of said survey were sent to interested landowners, namely J.W. Fitzpatrick, Adaline J. Moore, Frank Weaver, and William Weaver by registered mail, setting date of Nov. 12, 1926 for the beginning of the survey.

The survey was begun at the corner common to sections 7-8-17-18 in T 30 S, R 5 W, W.M. which corner was an iron pipe with old B.T.'s in evidence.

I thence ran a line South to the section corner common to sections 17-18-19-20 previously established by G.C. Stewart on a legal survey for J.M. Yokum and Edwin Weaver made on Dec. 16, 1921 and continued on April 1922 and recorded in Vol. 3 page 105 and 117 of the County Surveyors Record. This corner had been established by Stewart according to government instructions but Mr. Fitzpatrick questioned its location so I continued South to the 1/4 corner between Sections 19 and 20, the same being a corner set by Stewart from government P.T.'s.

I then went to the section corner common to sections 17-16-20-21 and ran west to the Section corner common to Sections 18-19 on the Range Line between ranges 5 and 6 West. This corner had been re-set by Stewart from Government B.T.'s.

I found the 1/4 corner between Sections 19/20 to be 7949.0 feet South and 231.3 feet West from the Section Corner common to sections 7-8-17-18. The Government field notes call for the distances as follows, Cor. 7-8-17-18 to 1/4 corner between 17-18, 40 chains; 1/4 corner between sections 17-18 to Section Corner 17-18-19-20, 40 chains; Section Corner 17-18-19-20 to 1/4 corner between Sections 19-20, 40 chains, hence the Section corner 17-18-19-20 should be $(7949.0 \times 2/3) 5299.3$ feet South of the Section corner 7-8-17-18.

I made the Southwest corner of Section 18 103.4 feet South and 11,063.8 feet West from the Section corner common to sections 16-17-20-21. The government field notes call the distance from the section corner common to sections 16-17-20-21 to the section corner common to sections 17-18-19-20 80.4 chains and the distance from the section corner common to sections 17-18-19-20 to the Southwest corner of section 18, 82.64 chains. The total distance between corner 16-17-20-21 and the southwest corner of 18 would then be $(80.4 + 82.64) 163.04$ chains. The corner common to sections 17-18-19-20 should then be $(80.4 : 163.04 :: x \text{ is to } 11,063.8) 5455.8$ feet West from the Section Corner common to Sections 17-16-20-21.

I made Stewarts corner to sections 17-18-19-20, 5505.4 feet South of corner common to sections 7-8-17-18 hence it should be moved North $(5505.4 - 5299.3) 206.1$ feet. I made ~~Stewarts~~ Stewarts corner to sections 17-18-19-20, 5232.5 feet West from the corner common to sections 16-17-20-21, hence it should be moved West $(5455.8 - 5232.5) 223.3$ feet.

However Stewarts Corner 17-18-19-20 was established on a legal survey as recorded in Vol. 3, pages 105 and 117 of the County Surveyors Records and has been accepted as the legal and true corner by residents, I also accept it as the true corner to Sections 17-18-19-20.

I then set the 1/4 corner between sections 17/18 on the true line between section corners 7-8-17-18 and 17-18-19-20 and midway between ~~between~~ said section corners.

I then ran a line from the established corner between sections 17/18 West to the West 1/4 corner of Section 18 on the township line which was in place. On this township line I also find the 1/4 corner for the East side of Section 13 north of the 1/4 corner for Section 18.

[Handwritten signature]