

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

Survey No.	Made on April 16 - 19 1928	Survey No.	Made on
In Town. 22 S Range 6 W	Sec. 13	In Town.	Range Sec.
Made for Hooper Bros.		Made for	
Purpose of To establish the west boundary of lands of Hooper Bros. in section 13.		Purpose of	

FN. "LL"

I first identified the section corner 13- 14- 23 and 24 from the original BT's which checked the original field notes except that the distance to an oak N 63° E should have been 233 lks instead of 133 lks. I renewed this corner by driving a 3/4" x 36" pipe and marking new BT's as follows:

- 14" Fir N45°E 31 lks. scribed S 13 T 22 S R 6 W CS BT
- 10" " S 35°E 13 lks. " S 24 T 22 S R 6 W CS BT
- 18" " S30° W 37 lks " S 23 T 22 S R 6 W CS BT
- 6" " N 85°W 26 lks. " S 14 T 22 S R 6 W CS BT

I then went to the SW corner of the Thomas Stillwell Donation Land Claim No 39 which I identified by a post set by a previous surveyor also by two original BT's ~~of~~ one of which carried scribe marks the marks on the other having been burned off. I found the bearings and distances to be S 15° E 30 lks and S 10° W 15 lks also a latter BT N 19° E 5 lks. I set a 1" x 30" pipe for the corner and remarked all BT's.

From the SW corner of DLC 39 just described I ran a traverse North to the NW corner of this claim. The location of this corner I identify from one of the original BT's which I had to cut down to find the scribe marks. This tree was a 50" fir S 80° W 26 lks from the corner. I drove a 3/4" x 36" pipe for the corner and mark two new BT's as follows:

- 14" fir S 80° W 73 lks scribed CL 39 CS BT
- 14" " S 84° E 82 lks " CL 39 CS BT this tree had been

scribed about 30 years ago.

From this corner I ran a traverse east 505 ft to the approximate SW corner of lot 5 of Sec 13 thence North along the approximate East line of Lot 5 to the approximate E and W line through the center of the section; thence west to the 1/4 section corner between sections 13 and 14. At this 1/4 sec corner I found a rock 6" x 10" x 15" set by Theil. I found an oak which had been burned and rotted out which appearantly had been the original BT also the roots of a fir which checked for the other BT. Mr Clayton was present and stated that he had seen this tree chopped out and at that time it carried scribe marks. They had since rotted. I marked new BT's

I then returned to the approximate NW corner of lot 5 and ran a traverse east and north to the 1/4 section corner between sections 12 and 13. At this point I found a square cedar stake and an Old BT N 14° E 33 lks. I reblaze this BT on the bark and scribe it 1/4 s 12 CS BT and blaze and scribe a 16" W oak South 94.8 ft 1/4 S 13 CS BT for a new BT.

From the approximate SE corner of Lot 5 I made a triangulation into a field near the south line of section 13 and then to the interior corner of DLC 39 and the 1/4 section corner between secs 13 and 24. The interior corner of the DLC is at a fence corner and its location is correct with reference to both original BT's which are standing