

277
COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

PUSHORE & CO. PORTLAND, ORE. S. 545

Survey No. **V6-E62** Made on **May 22 & 23, 1929.**

In Town. **26 S. Range 3 W. Sec. 9**

Made for **H. C. Wood.**

Purpose of establishing the West & North Lines of the South-East $\frac{1}{4}$ of Section 9

Survey No. **V6-E63** Made on **May 3-4-5 1929.**

In Town. **30 S. Range 3 W. Sec. 5**

Made for **William Rachor.**

Purpose of Establish the South Line of D. L. C. No. 38 and the Line between Sections 5 & 6.

F.N.L.L.

F.N.L.L.

I began survey at the S $\frac{1}{16}$ Corner, being the SW Corner of the NW $\frac{1}{4}$ of SE $\frac{1}{4}$ of Section 9, marked by a Standard U. S. Survey pipe Corner, from which a Cedar 18 inches in Diam. bears N. 44° E. 9 links, marked S. $\frac{1}{16}$ S. 9 B. T.

I sighted on a U. S. Standard pipe, angle point on power reserve in the e edge of the County road, said pipe marked A. P. 1. P. R. and on this line I ran N. 0° 55' W. 20.837 chains to the center of Section 9, marked by a U. S. Standard pipe corner, marked C. $\frac{1}{4}$. S. 9, from which a B. Oak 10 inches in dia. bears N. 49° W. 8 links and a black oak 10 ins. in dia. bears S 20° E 7 lks.

From this center of section I ran N 89° 48' E and at 13.72 chain cross County road along the North Umpqua River, thence across river 10 chains to the right bank, and at 30.48 chains hit river again on the right bank, thence across the river to the $\frac{1}{4}$ corner on the left bank of river, an oak post set in rock on steep bank of river, from which a fir 8 ins. dia. bears N 27° E 11 lks and a fir 12 ins. dia. bears N 65° W 16 links.

N. E. Richardson and B. A. Lane, chairman

H. C. Wood, axe

H. L. Epstein
 County Surveyor

I Began the Survey at the Section Corner Common to Sections 5 & 6 in T. 30 S. R. 3 W. W. M., Thence N. 0° - 28' E 5103.9 feet to the Section Corner of Sections 5 - 6 - 31 & 32 on the Township Line, which I replace from one old Bearing Tree, Oak N. 65° E 98 links, other trees gone.

Thence I went to a South-East Corner of D. L. C. No. 38 in the above T. and R. which I establish from the old Bearing Trees, Fir N. 50° W. 12 links, scribe marks plain and Laurel in evidence, no scribe marks. Thence I ran West and at 3183.8 feet hit the South West Corner of said Claim, which I set from Old Bearing Trees, a Fir N. 30° W. 58 links, cut down but B. T. in stump and plain, other tree a Fir S 60° W. 75 links, stump there but scribe marks rotted out.

At the intersection of the Section line between Sections 5 & 6, with the South Line of D. L. C. No. 38. I set a $\frac{1}{2}$ " x 24" Iron Pipe for Rachor's North-West Corner from which a 6" apple tree bears S. 3° - 30' W. 67.0 feet, said Corner being West 2409.5 feet from the South-East Corner of Claim 38 and N. 0° - 28' E. 1340.8 feet from the Corner of Section 5 & 6.

Chainmen B. A. Lane and Henry Rachor, Axe William Rachor, John Busenbark present part of the time.

H. L. Epstein
 County Surveyor