

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHORE & CO. PORTLAND, ORE. 87545

<p>Survey No. <b>4</b> Made on Feb. 17 -Mar. 8 1930</p> <p>In Town. 30 S Range 3&amp;4 W Sec. 30 and 25</p> <p>Made for Vernon Poole, Delbert Poole, Joe Wright, Roy Mathews, Henry Bigham, D. Burnett.</p> <p>Purpose of Establishing lines and making deed descriptions.</p> <p style="text-align: right;">Ben. B. Irving, Deputy County Surveyor.</p> <p>C. S. File No. <u>37/18</u> MAP FILE <u>M1-1-27-3</u></p>	<p>Survey No. _____ Made on _____</p> <p>In Town. _____ Range _____ Sec. _____</p> <p>Made for _____</p> <p>Purpose of _____</p>
---	--

This work was begun at a pile of rock as set by Frank Cain as being the approximate N center 1/16 section corner of Section 30. A traverse was then ran for the description of the area to be deeded from Allen to Vernon Poole. The tie was run from the corner shown on the accompanying map as 24 to the 1/4 section corner between sections 30 and 31. From this it was discovered that there was considerable doubt as to the position of the beginning point, and it was decided to defer the description until a further check could be made by running the other lines of the section.

From the 1/4 section corner on the south side of section 30 which I found as recorded in the County Surveyor's office I ran a Traverse westerly to the Section corner at the SW corner of section 30. I then computed this line to be N89°37'W 43.388 chains. The SW corner of section 30 I identify from three of the original BT's and I renew the corner as indicated on the accompanying map. I then ran a traverse from the SW corner of section 30 southerly to the closing corner between sections 25 and 36 on the range line. I find by computation that this line bears S 0°37'W 28.803 chains. This corner is as shown by the records of the Public Survey Office except that the post had fallen down. I place a new post and drive the old one alongside.

I then return to the SW corner of Section 30 and ran northerly a traverse to the 1/4 section corner on the west side of section 30 and to the closing section corner on the range line for the corner between sections 24 and 25. The 1/4 section corner on the west side of section 30 was gone but I find the one BT standing and the stump of another. Figures very plain on being chopped out. I renew this corner as indicated on the map. The line between the SW corner of 30 and the 1/4 section corner bears N 1°25'E 38.286 chains. The closing section corner between sections 24 and 25 was identified from one original BT and the corner post of a property line. It was renewed as shown on the map attached. The bearing of the line between the 1/4 section corner of section 30 and this section corner I find to be N 1°56'E 10.998 chains.

I now return to the approximate corner for the SE corner of the Jacob Amsler Donation Land Claim No 39 as pointed out by Vernon Poole who had seen it before being destroyed and ran a traverse westerly. The SW corner of the claim on the bank of the river was missing so I continue the traverse Northerly to the NW corner of the claim. Here both original BT's are standing although one is badly rotted. I renew this corner as shown on the map and determine the location of the SW corner and the true position of the SE corner from the bearing and distances of the traverses from the corner found and a line tree the stump of which I am able to identify on the south line of the claim. I renew both corners as indicated on the map.

From the information now available I compute and set the closing 1/4 corner on the east side of section 25 and the intersection of the south line of the Donation Land Claim and the Range line. The description of these corners are given on the attached map. I also compute the location of the corners of the 10 acre tract belonging to D. Burnett (the westerly 10 acre of lot 8 of section 30) and set them as shown on the map.

I next go to the 1/4 section corner on the east side of section 30 and run a traverse west to the 1/4 section corner on the west side of section 30. The original BT's for the east 1/4 section corner of section 30 are in excellent condition and I remark them and set a new post. From this traverse and a traverse connecting the North and South 1/4 section corners of section 30 I compute the intersection of the center lines of the sections and set the center 1/4 section corner ~~and~~ then compute and set the north and south 1/16th section corners of the center lines. These corners are described on the attached map. I also ran a traverse along the bank of the river and determined as nearly as may be the position of the center of the river for deed descriptions using said center of the river as the property boundary between Vernon Poole and Delbert Poole. I also computed ~~the~~ the area and ~~description~~ description for the area to be deeded from Allen to Vernon Poole.

In order to determine the location of the line between lots 1 and 2 of section 25 and the Donation Claim of Jacob Amsler I started at the NW corner of said claim and ran a traverse easterly to the NE exterior corner. From this traverse I compute the bearing and distance of this line and also its intersection with the range line.