

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BRUNSON & CO. PORTLAND, ORE. 87545

Survey No.	Made on June 10 to 24 1930	Survey No.	Made on
In Town. 333	Range 5 W Sec. 2	In Town.	Range Sec.
Made for	Frank Kruse et al	Made for	
Purpose of	To establish the North line and the east and west and north and south centerlines of section 2. also the North line of the Quartz Mill Mine.	Purpose of	
C. S. File No.	37/23		

MAP FILE RM 11-11-3

On June 10 1930 I commenced the survey at the NE corner of Section 2 T 33 S R 5 W M. This corner was an Iron Pipe which was driven by CO Garrett at the point where the corner post previously stood. I checked this location from the Bearing Trees as described in the Government Field Notes. One of the BT's having been cut I blazed and scribed a 12" fir S 32° W 46 lks ~~XX~~ T33SR5W CO S2 CS BT in lue thereof. I also reblaze and scribe the remaining original BTs.

From the above corner I ran a traverse westerly. I failed to locate the $\frac{1}{4}$ section corner of Section 35 T 32 S R 5 W so continued to the SW corner of said section 35. ~~XXXXXX~~ This I find as described in the Government Field Notes of 1894. I also found the Original BT a 50" fir as described in the Field Notes of 1854. I then continued westerly to the Closing Section Corner to Sections 2 and 3 of T 33 S R 5 W which I find to be as described in the government field Notes. I reblaze and scribe the BT's as found for both the SW corner of Section 35 and the closing corner of section 2 and 3

I then returned to the location of the $\frac{1}{4}$ section corner of section 35 and after further search locate the corner post as described in the field notes of the U.S. Deputy Surveyor of 1901. The post is rotted off and only the 50" fir BT S 52° E 71 lks remain. I renew this corner by driving a $1\frac{1}{4}$ inch iron pipe for the corner and placing a Yew wood post alongside properly scribed from which a 16" fir bears N13° W 108 lks Blazed and scribed $\frac{1}{4}$ S 35 CS BT. ; I also reblaze and scribe the original BT.

With the above data at hand I compute the the line from the NE corner of Section 2 to the $\frac{1}{4}$ section corner of Section 35 to bear N 89° 38' W 36.06 chs. The line from the $\frac{1}{4}$ section corner of section 35 to the SW corner of section 35 bears N 89° 46' W 40.457 chs and the line from the SW corner of section 35 to the NW corner of section 2 bears S 89° 43' W 5.044 chs. The total distance from the Ne to the NW corners of Section 2 is 81.56 chs.

At the mid point between the NE and NW section corners of section 2 and on the line between the $\frac{1}{4}$ section corner and the SW corner of Section 35 I locate the Closing $\frac{1}{4}$ section corner of Section 2. This is a $1\frac{1}{4}$ " iron pipe with a Yew wood Post along side and from which a 20" fir bears S 58° E 64 lks. and a 20" fir bears South 73 lks.

I then returned to the NE corner of Section 2 and ran a traverse South to the $\frac{1}{4}$ section corner between section 1 and 2. This I found to be as described in the government field notes. This line bears S 0° 11' W 42.353 chs. By proportional measurement I locate for the 1/16th section corner a $1\frac{1}{4}$ " iron pipe 20.891 chs from the $\frac{1}{4}$ section corner from which a 14" Yew wood bears S 75° W 16 lks and a 14" maple bears N 70° E 22 lks Blazed and scribed N 1/16 S 2 CS BT and N 1/16 S 1 CS BT respectively. Also at a point 1500 ft. North of the $\frac{1}{4}$ section corner between secs. 1 and 2 I locate for the NW corner of the Quartz Mill Mine a $1\frac{1}{4}$ " iron pipe from which a 30" cedar bears S 62° E 26 lks and an 8" fir bears N 52° W 40 lks both blazed and scribed NW Cor QM CS BT.

From the NW corner of the of the Quartz Mill Mine I ran East 600 ft and located the NE corner of the mine which is a $1\frac{1}{4}$ " iron pipe from which a 12" cedar bears S 60° W 9 lks and a 10" cedar bears N 2° W 6 lks both blazed and scribed NE Cor QM CS BT.

I then returned to the Closing $\frac{1}{4}$ section corner on the North side of section 2 and ran a traverse South to the $\frac{1}{4}$ section corner between sections 2 and 11 which I find to be as described in the government field Notes. I reblaze and scribe the BTs. I find this line to bear S 0° 2' W 81.096 chs.

Thence from the $\frac{1}{4}$ section corner between sections 1 and 2 I ran a traverse westerly to the $\frac{1}{4}$ section corner between sections 2 and 3 which I find to be as recorded in the government Field Notes. I find this line to bear N 88° 27' W 81.456 chs.

At the intersection of the center lines through section 2 I locate a $1\frac{1}{4}$ " iron pipe for the center $\frac{1}{4}$ section corner of section 2 with a Yew wood post along side from which a 6" fir bears East _____ lks and an 8" fir bears West 35 lks.

The attached map illustrates the results of this survey and forms a part of this record.

Ben. B. Irving
Ben. B. Irving
Deputy County Surveyor.